

AUCA00355 Cabot's Composite Cleaner

Introduction

SKU
57BW0554-1L
57BW0554-4L

Description and Image

Cabot's Composite Cleaner is an easy to use, effective cleaning solution for everyday use. It removes grease and grime and is compatible with all capped and uncapped composite types, including vertical and horizontal surfaces. It is also safe for plants*, and has a great Eucalyptus scent. It does not contain bleach or harsh solvents.



Features and Benefits

- Removes Grease & Grime
- Safe for Plants (when used diluted and in accordance with instructions)
- Fast & Easy to Use
- Water Wash Up

Uses

For use on all types of composite including capped and uncapped vertical or horizontal surfaces

Precautions and Limitations

Do not use Cabot's Composite Cleaner within 12 weeks of coating your composite decking.

Performance Guide

Weather Not Applicable	Heat Resistance Not Applicable
Water Not Applicable	Abrasion Not Applicable

Typical Properties											
Colour	Pale yellow										
Components	1 pack										
Mixing Ratio	1:10										
Clean Up	 Water										
Clean Up Description	Clean brushes and equipment with water. Dispose of contents/container in accordance with local, regional, national and international regulations.										
Application Methods	 Brush Cabot's Deck Prep Brush										
Application Conditions	<table border="1"> <thead> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td><input type="text"/></td> <td><input type="text"/></td> <td>40</td> </tr> </tbody> </table>				Min	Max	Recommended	Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	40
	Min	Max	Recommended								
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	40								
Typical Property Notes	Will cover up to 40 m ² /L when diluted.										

Application Guide
<p>Surface Preparation</p> <p>To prepare your composite deck for cleaning, sweep away leaves, dirt and debris. Hose down composite surface, ensuring it is damp prior to application of Cabot's Composite Cleaner.</p>
<p>Application Procedure and Equipment</p> <ol style="list-style-type: none"> Shake contents before use. Mix the product in the Cabot's Deck Hand Bucket with water with a 1:10 ratio (1 part cleaner, 10 parts water). Apply generously to the surface with Cabot's Deck Prep brush. Scrub vigorously. For best results, leave the solution on the surface for 5-10 minutes. Do not allow to dry on the surface. If required, add more product onto surface to keep it from drying. Lightly scrub the surface before rinsing, then rinse off with water using a high-pressure or garden hose. Heavily soiled or very dirty surfaces may require repeat application. If using a high pressure hose or power washer, use the lowest setting to avoid damaging the surface.

Health and Safety	
SDS Number DLXGHSEN004819	SDS Link View SDS Link
<p>Using Safety Precautions Risks: Undiluted form may cause an allergic skin reaction and serious eye damage.</p> <p>Keep out of reach of children. Read carefully and follow all instructions. Wear protective gloves/protective clothing including eye/face protection. If medical advice is needed, have product container or label at hand.</p> <p>IF ON SKIN: Wash with plenty of water and soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
Pack A 57BW0554	
Size: <input type="text" value="1L, 4L"/>	Weight: <input type="text" value="1.092Kg, 4.198Kg"/>
<p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p>	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.