

AUFW00089 Feast Watson Stain & Varnish Liming White Satin

Description and Image

Feast Watson Stain & Varnish Liming White is a water based timber stain combined with a professional clear polyurethane. Stain & Varnish Liming White gives a soft, milky white effect to timber and simultaneously preserves the stain by protecting it with a durable clear finish. The water based formula is non-yellowing, and imparts colour without obscuring the natural characteristics of the timber grain. One coat gives a subtle, pale colour; multiple coats will build the opacity and whiteness. Stain & Varnish Liming White is convenient to apply as it is fast drying, low odour and all application equipment can be cleaned up with water. It is ideal for use on all interior furniture and woodwork

Features and Benefits

- Liming white stain combined with a professional clear polyurethane.
- Water based.
- One step stain and varnish.
- Non yellowing, low odour, fast drying, with easy water wash up.

Uses

All interior timber furniture

Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.

Performance Guide

Weather Interior Only	Heat Resistance Softens at temperatures above 70C
Water Good water resistance, unaffected by splash or spillage	Abrasion Good Resistance to Abrasion

Typical Properties			
Gloss Level Satin		Heat Thinner Water	
Colour Liming White			
Components 1		Number of Coats 1+	
Toxicity Lead Free		V.O.C. Level <70 g/l	
Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry 30 minutes			
Clean Up  Water			
Application Methods  Brush  Roller  Pad			
Application Conditions		Solids by Volume	
		26	
	Min	Max	Recommended
Wet Film Per Coat (microns)	83	125	100
Dry Film Per Coat (microns)	22	33	26
Recoat Time (min/hours)	2 Hours	Indefinite	2 hours +
Theoretical Spread Rate (m ² /L)	8	12	10
Typical Property Notes Drying time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 30 minutes. Recoat: 2 hours. Allow 24 hours before light foot traffic and 72 hours for normal traffic. Full curing after 7 days.			
Coverage Softwood: 8 - 10m ² per litre. Hardwood: 10 - 12m ² per litre. Cork: 8 - 10m ² per litre.			

Application Guide

Surface Preparation

New or bare timber/cork

Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson Sanding Sealer and sand back as per the directions.

Previously Coated Timber

Previously coated surfaces need to be sanded back to bare timber. Remove all sanding dust before coating.

Application Procedure and Equipment

Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. Stain & Varnish Liming White should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.

Apply Stain & Varnish Liming White using a brush, roller or spray. If spraying Stain & Varnish Liming White may be thinned by using 10% water. If applying by roller, use a short nap (5mm) mohair roller. Ensure edges and end grain are fully coated. Three coats of varnish are required. If the desired colour is achieved with the first coat, complete the following coats with a suitable water based clear coating, such as Cabot's Carbothane clear water based or Intergrain Ultraclear Interior as additional coats of Stain & Varnish Liming White will intensify the colour. Allow 2 hours drying between coats.

Sand lightly between coats with a fine sandpaper. If applying over a previous varnish coating, two coats will be sufficient. For new timber, and if applying by spray, apply a minimum of three coats. More coats may be applied for extra durability. Do not apply in temperatures under 10°C or above 35°C.

Health and Safety

SDS Number
22937

SDS Link
[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
917W0053

Size:

1L, 250mL

Weight:

1L = 1.2kg, 250ml = 0.33 kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.