

AUPR00017 Dulux Professional Interior/Exterior Acrylic Matt

Introduction

Part A

609-89852 (White), 609-89926 (DTB) & 609-89927 (UDTB)

Approvals

APAS 0260/4 (White Base only)

Description and Image

Dulux Professional Matt Interior/Exterior Acrylic is a premium, washable and scrubbable, hard wearing, new generation acrylic for use on interior and exterior broad wall areas. This product has been formulated to have excellent application and touch up performance, and is ideally suited to jobs where critical light and/or surface texture are less than ideal. All Dulux Professional products are designed to meet the application needs of painters.

Features and Benefits

- Water Based
- Super acrylic paint
- Ease of Application
- Low side sheen
- Same Day recoat, easy clean up
- Provides hardwearing properties
- Easy spreading and lapping on broadwall areas
- Hides substrate imperfections

Uses

Use Dulux Professional Interior/Exterior Matt Acrylic as a subdued broad-wall finish on all interior and exterior surfaces. Particularly recommended to reduce the appearance of surface imperfections, particularly on surfaces with strong lighting.

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not use at temperatures below 10C, or when the temperature of the surface may fall below 10C during the drying period. Although the film is dry to touch in 30 minutes allow 7 days for film to fully cure before washing.

Tinted Colours

Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use. Darker colours will show more signs of marking and scuffing than lighter colours - if you are considering using a dark colour in a high traffic area you may want to consider a higher sheen level or the use of a protective clear coat.

Performance Guide

Weather

Designed for interior and exterior use.

Heat Resistance

Softens and sticks to other painted surfaces over 70C.

Water






Not recommended for high steam and condensation areas.

Solvent

Sensitive to aromatic hydrocarbons, alcohols and ketones.

Abrasion

Good wet and dry burnish resistance.

Typical Properties			
Gloss Level 2-6 at 60 degrees, 4-10 at 85 degrees		Thinner Water	
Colour White, Deep, Ultra Deep			
Components 1			
Toxicity Lead free. Dry film is non-toxic.		V.O.C. Level < 40g/L untinted	
Touch Dry 30 Minutes			
Clean Up  Water			
Clean Up Description Clean all equipment with water			
Application Methods  Air Spray  Airless Spray  Brush  Roller			
Application Conditions		Solids by Volume	
		<input type="text" value="36"/>	
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="68"/>	<input type="text" value="68"/>	<input type="text" value="68"/>
Dry Film Per Coat (microns)	<input type="text" value="25"/>	<input type="text" value="25"/>	<input type="text" value="25"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="14.6"/>	<input type="text" value="14.6"/>	<input type="text" value="14.6"/>

Application Guide

Surface Preparation

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Apply suitable prepcoat.

Application Procedure and Equipment

Stir contents thoroughly before and during use with a broad flat stirrer using an upward action.

Brush/Roller

Use a medium nap roller (12mm). Pre-wet brushes and rollers with water before commencing application. Avoid excessive brushing or rolling back into the paint which has been drying for more than 3 minutes. Thinning not usually required however, if necessary, thin with up to 100 ml of water per litre to ease application. Under hot conditions up to 60 ml per litre of Dulux Hot Weather Thinner may be used.

Airless/Conventional Spray

Suitable for application by all standard spray equipment. If necessary, thin up to 125ml per litre with clean water to aid atomisation.

Health and Safety

SDS Number

21463, 0

SDS Link

[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

609-89852 (White), 609-89926 (DTB) & 609-89927 (UDTB)

Size:

Weight:

4Litre 10 Litre 15 Litre

5.5Kg 13.7Kg 20.5 Kg

Flash Point

NA

UN Number

NA

Dangerous Goods Class

NA

Package Group

NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.