

AUCA00001 Cabot's Floor Polish Gloss

Introduction

Part A
918-82162

Description and Image

Cabot's Floor Polish is the easiest way to restore, enhance and protect timber flooring. It prolongs the life of timber coatings and is designed specifically for coated timber, parquetry and cork floors.



Features and Benefits

- Rejuvenates and protects.
- Adds shine.
- Easy to apply.
- Fast drying - 1 hour.
- Resists knocks and wear and tear from foot traffic helping extend the life of your floor coating.
- Restores and protects the original gloss and enhances the appearance of the floor.
- Application is easy with a lambswool applicator or sponge mop.
- Normal use of the floor in 1 hour.

Uses

Pre-coated interior timber, parquetry and cork floors. It may also be used on sealed vinyl, slate and ceramic tiles.

Precautions and Limitations

Do not apply this product if the temperature is below 10°C or above 35°C.

Performance Guide

Weather Interior only.	Heat Resistance Up to 50C
Water Good.	Abrasion Good.

Typical Properties

Gloss Level

Gloss

Colour

Clear

Components

1

Number of Coats

1 - 2

V.O.C. Level

< 95g/L

Touch Dry

30 minutes

Clean Up



Water

Application Methods



Brush



Pad

Application Conditions

Solids by Volume

16

Min

Max

Recommended

Wet Film Per Coat (microns)

19

Dry Film Per Coat (microns)

3

Recoat Time (min/hours)

1 hour

Theoretical Spread Rate (m²/L)

60

Typical Property Notes

Spreading rate

Up to 60 square metres per litre.

Drying and re-coat time

All timings quoted at 25°C and 50% humidity. Cooler or humid conditions may require longer.

Walk on and normal traffic After 1 hour.

Application Guide

Surface Preparation

Floor Polish should only be applied to a dry and well cured surface (a new coating should be at least 4 weeks old). Ensure the surface is thoroughly cleaned with Cabot's Floor Clean prior to using Cabot's Floor Polish.

Application Procedure and Equipment

Applicator or mop

Important Do not shake before use.

Apply Cabot's Floor Polish with a sponge mop or lambswool applicator. Use gentle application to avoid bubbles and do not allow pools of liquid to form. Allow the surface to dry for 1 hour. Repeat application if a higher gloss level is desired.

Walk on and normal traffic After 1 hour.

Maintenance

Wash your floor regularly using Cabot's Floor Clean to remove dirt and grime. When the surface looks worn, re-coat with Cabot's Floor Polish as a regular maintenance solution.

Removing Cabot's Floor Polish

If required, old layers of the polish may be stripped off using Cloudy Ammonia; this should be available in hardware stores and supermarkets.

- Apply undiluted Cloudy Ammonia to the floor.
- Leave for 5 minutes.
- Do not allow the Cloudy Ammonia solution to dry out.
- Do not flood the floor with the solution.
- Mop up solution and then thoroughly clean surface with a clean mop and fresh water.
- Repeat if necessary.
- Allow surface to dry.

Once the old polish has been removed, a new coat of Cabot's Floor Polish can be applied, following the label instructions.

Health and Safety

SDS Number

144402

SDS Link

[View SDS Link](#)

Using Safety Precautions

Store in a cool, dry, well ventilated place and out of direct sunlight. Keep containers closed when not in use.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

918-82162

Size:

Weight:

1L

1.2Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.