

AUPR00024 Dulux Professional Acrylic Sealer Undercoat

Introduction

Part A
664-84191

Approvals
APAS 0172 (CLASS II)

Description and Image

Dulux Professional Acrylic Sealer Undercoat is a super acrylic paint with excellent opacity, adhesion, sealing, filling and flow. It is suitable for interior areas, particularly new walls and ceilings.

Features and Benefits

- Extremely high opacity
- Excellent adhesion
- Recoatable with all systems
- Water based
- Sticks to substrates increasing life of paint system.
- Use under acrylic or oil based topcoats, 1 product does it all.
- Easy clean up, low odour.

Uses

Use Dulux Professional Acrylic Sealer Undercoat as a quick drying sealer undercoat on interior masonry, paper faced wallboards and suitably primed timber and metal. Suitable for both oil based and water based top coats.

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not overspread or exceed 12.0 square metres per litre per coat. In hot weather, rinse brush every half hour or use two and keep one standing in water. Do not apply if temperature is under 10C, or when temperature of surface may fall below 10C during the drying period, otherwise film formation will not be complete and a fall-off in properties will result.

Performance Guide

Weather

Not recommended for exterior use.

Heat Resistance
Up to 70C.






Water

Excellent when topcoated with approved topcoat.

Solvent
Sensitive to aromatic hydrocarbons, alcohols and ketones.

Abrasion

Good when topcoated.

Typical Properties			
Gloss Level Flat		Thinner Water	
Colour White, may be tinted up to 25ml per litre.			
Components 1			
Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.		V.O.C. Level <30 g/L inclusive of Dulux Low VOC tinter.	
Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry 30 Minutes			
Clean Up  Water			
Clean Up Description Clean all equipment with water.			
Application Methods  Air Spray  Airless Spray  Brush  Roller			
Application Conditions	Solids by Volume		
	<input type="text" value="39.1"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="72"/>	<input type="text" value="72"/>	<input type="text" value="72"/>
Dry Film Per Coat (microns)	<input type="text" value="28"/>	<input type="text" value="28"/>	<input type="text" value="28"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m²/L)	<input type="text" value="14.0"/>	<input type="text" value="14.0"/>	<input type="text" value="14.0"/>

Application Guide

Surface Preparation

All surfaces must be thoroughly clean and free of all loose dirt, grease, mould, surface chalk and loose or flaking paint. Suitable for use on plasterboard, interior masonry such as cement render or brickwork and as an intermediate coat over suitably primed timber and metal. For plaster surfaces use a sealer binder or oil based undercoat.

Application Procedure and Equipment

Brush, roller, conventional or airless spray

Stir contents thoroughly before and during use. Apply direct from the can. May be applied to dampened surfaces. If applied over dry, porous surfaces, dampen surface before applying.

Brush

Wet brushes with water prior to use to avoid clogging. Apply a full even coat direct from the container. Under hot conditions it may be necessary to thin with up to 100ml per litre of clean water.

Roller

Using a medium nap roller apply a full even coat direct from the container and finish by light parallel strokes with a dry roller.

Airless/Conventional Spray

Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.

Health and Safety

SDS Number
DLXGHSEN001183

SDS Link
[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
664-84191

Size:

4 Litre 10 Litre 15 Litre

Weight:

6.4 Kg 15.8 Kg 23.4 Kg

Flash Point

NA

UN Number

NA

Dangerous Goods Class

NA

Package Group

NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.