AUFW00113 Feast Watson Timber Floor Paint

Introduction

Part A
710W0051 WHITE; 710W0052 ULTRA DEEP BASE

Description and Image

Feast Watson Timber Floor Paint is an opaque, water based coating for interior timber floors. Timber Floor Paint has been specifically formulated to provide superior abrasion resistance and delivers outstanding adhesion for longer lasting results. Timber Floor Paint can used on new and existing interior timber, cork and parquetry floors. It is ideal for interior timber flooring subject to high wear, and can be tinted to a wide range of colours.



Features and Benefits

- Opaque, water based coating for interior timber floors
- Superior abrasion resistance
- Tint to a wide range of colours

Uses

Use on new and existing interior timber, cork and parquetry floors

Precautions and Limitations

Do not apply this product at temperatures below 10°C or above 35°C.

Performance Guide

Weather
Interior only

Abrasion
Very good

Typical Properties

Gloss Level
15-30% measured at 60 degrees

Heat Thinner
Water

Colour
Available in White and tinted colours

Number of Coats
2-3

V.O.C. Level
<65g/L

Meets GBCA V.O.C. Requirements?
Yes

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.

Touch Dry
30 minutes

Clean Up
Water

Application Methods
Brush **Roller** **Pad**

Application Conditions

Solids by Volume: 33

	Min	Max	Recommended
Recoat Time (min/hours)	2 hours		
Theoretical Spread Rate (m²/L)	8	12	

Typical Property Notes

Coverage
Softwood: 8 - 10m2 per litre.
Hardwood: 10 - 12m2 per litre.
Cork: 8 - 10m2 per litre.

Drying time
Drying times are given at 25°C and 50% relative humidity. Lower temperatures and higher humidity can lead to extended drying times.
Touch Dry: 30 minutes.
Recoat: 2 hours.
Allow 24 hours before light foot traffic and 72 hours for normal traffic. Full curing after 7 days.

Application Guide

Surface Preparation

New or bare timber/cork
Punch exposed nails below the surface. Holes and imperfections should be filled with timber putty.
Sand timber to an even, smooth surface. Vacuum and wipe to remove dust.
Prepare uncoated cork tiles in accordance with the supplier's recommendation.
Seal bare timber with 1 coat of Feast Watson® Proofseal. Apply according to label instructions.

Previously coated surfaces
Clean surface with Feast Watson® Floorclean™ and allow to dry.
Sand surface thoroughly until a uniform matt appearance is achieved.
Vacuum and wipe to remove dust.
Check adhesion by applying Timber Floor Paint to a small test area. Allow to dry for 24hrs then firmly press a strip of sticky tape over the test area and rip off quickly. If coating is removed, it will not adhere to the surface so the surface needs to be sanded back to bare timber or cork. If coating is not removed, sand the test area back to a uniform matt surface.
If previous coating has worn back to expose bare timber or cork it must be completely removed.

Application Procedure and Equipment

Surfaces to be coated must be dry and free from all dirt, dust, grease, wax, polish and oil.
Timber Floor Paint should be mixed thoroughly, with a flat blade stirrer, before and during application, taking care not to introduce bubbles.
Apply with a Feast Watson® Floor Finish Applicator, brush or short nap roller. Work along the whole length of 3 - 4 floorboards at a time, maintaining a wet edge to prevent lap marks. Ensure final brush strokes are in the direction of the grain. Take care to not introduce bubbles.
When the first coat is thoroughly dry, apply second coat as outlined above.

Note, if grain raising is present a light sand is required before the second coat.

For a longer wearing finish apply a third coat as per previous instruction.
If a gloss finish is required, apply a suitable gloss water based floor coating, such as Cabot's® CFP Water Based as per label instructions.

Do not apply this product at temperatures below 10°C or above 35°C.

Thinning
In hot temperatures (over 30°C) thin with up to 100mls of water per litre to ease application and slow drying.

Maintenance
Regularly clean using Floorclean™.
Monitor the surface for signs of colour loss or surface defects. When floor requires an additional coat of Timber Floor Paint, apply as per the instructions for Previously Coated Surfaces.

Health and Safety

SDS Number	SDS Link
DLXGHSEN000260	**View SDS Link**

Using Safety Precautions
Keep out of reach of children. Avoid contact with skin and eyes or breathing vapour and spray mist. Wear waterproof gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Slippery when spilt; clean up immediately.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
710W0051 White; 710W0052 Ultra Deep Base

Size:	Weight:
4L White 4L Ultra Deep Base	**5.30kg 5.00kg**

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information

Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.