

AUFW00041 Feast Watson Weatherproof Varnish Satin

Introduction

Part A
870 94995

Description and Image

Feast Watson Weatherproof Varnish is a clear, polyurethane timber finish that provides excellent timber protection against the elements. Incorporating UV screening, Weatherproof Varnish provides a tough clear finish that is resistant to sunlight, salt water, chemicals, oils and solvents. Available in satin and gloss. Weatherproof Varnish can be applied to exterior and interior timber window frames, doors, trims, panelling, boat handrails and furniture. Weatherproof Varnish can also be used to give Feast Watson Wood Shield oil a gloss or satin finish.

Note Weatherproof Varnish is not suitable for heavy wear surfaces (such as decks and walkways). For these areas use Feast Watson Decking Oil or Feast Watson Decking Stain.



Features and Benefits

- Clear timber finish.
- UV screening.
- Highlights timber beauty.
- Resistant to sunlight, salt water, chemicals, oils and solvents.
- Weather resistant.

Uses

Exterior and interior timber window frames, doors, trims, panelling, boat handrails and furniture.

Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.

Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.

Weatherproof Varnish is not suitable for heavy wear surfaces such as decks and walkways. For these areas use Feast Watson Decking Oil, Traditional Timber Oil or Timber & Deck Stain.




Weatherproof Varnish is also not recommended for exterior broadwall areas such as cladding and weatherboards.

Performance Guide

Weather
Exterior durable.

Heat Resistance
Up to 100C

Water
Excellent.

Typical Properties			
Gloss Level 40-50% at 60 degrees			
Colour Clear			
Components 1		Number of Coats 3 minimum	
Toxicity Lead free		V.O.C. Level < 455g/L	
Meets GBCA V.O.C. Requirements? No			
Touch Dry 4 hours			
Clean Up Description Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> Brush</div> <div style="text-align: center;"> Roller</div> <div style="text-align: center;"> Spray</div> </div>			
Application Conditions		Solids by Volume	
		<input type="text" value="41"/>	
		Min	Max
Recoat Time (min/hours)	<input type="text" value="12 hours"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="8"/>	<input type="text" value="12"/>	<input type="text"/>
Typical Property Notes Coverage Softwood: 8 - 10m ² per litre. Hardwood: 10 - 12m ² per litre. Drying Time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 4 hours Recoat: 12 hours			

Application Guide
<p>Surface Preparation</p> <p>New Timber Allow new timber to acclimatise in its final position for 4-6 weeks. Coat with Feast Watson Timber Primer to protect it from stains and warping during the acclimatisation period. Prepare exterior timber for coating with Feast Watson Woodclean as per the instructions. Sand to a smooth surface and remove all sanding dust before coating.</p> <p>Weathered Timber Prepare exterior weathered or grey timber by cleaning thoroughly with Woodclean as per the instructions. Sand to a smooth surface and remove all sanding dust before coating.</p> <p>Previously Coated Timber Previously coated surfaces need to be taken back to bare timber by sanding timber to a smooth surface. Remove all sanding dust before coating.</p>
<p>Application Procedure and Equipment</p> <p>Weatherproof Varnish should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. Apply Weatherproof Varnish using a brush, roller or spray. If spraying Weatherproof Varnish may be thinned by using 10% mineral turpentine. If applying by roller, use a short nap (5mm) mohair roller. Ensure edges and end grain are fully coated. Apply minimum three coats. Four or more coats may be applied for extra durability, or when the coating has been thinned. Allow 12 hours drying between coats. Sand lightly between coats. The final coat should be applied within 30 hours of the previous coat to ensure timber is protected.</p> <p>Maintenance Regularly monitor the surface for signs of colour loss or surface defects. When required, lightly sand the surface and remove dust. Re-coat with additional coats of Weatherproof Varnish as per application instructions.</p>

Health and Safety	
<p>SDS Number DLXGHSEN003603</p>	<p>SDS Link View SDS Link</p>
<p>Using Safety Precautions Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
<p>Pack A 870 94995</p>	
<p>Size: <input type="text" value="500ml 1L 4L"/></p>	<p>Weight: <input type="text" value="0.58Kg 1.08Kg 4.11Kg"/></p>
<p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p>	

Further Information
<p>Product page</p>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.