AUCA00349 Cabot's Laminate Floor Polish

Introduction

Part A
57MW0557

Description and Image

Cabot's Laminate Floor Polish has been developed to reduce the appearance of scratches, marks and scuffs on sealed laminate, vinyl, linoleum, cork flooring, polished concrete, slate or ceramic tiles. It can also be used on laminate, melamine, vinyl, sealed marble, MDF and particle board cupboards and furniture surfaces. It not only enhances appearance by reducing scratches and marks but also creates a protective layer that helps prolong the life of coated surfaces.

Whether you're wanting to make laminate floors shine again or after the best polish for laminate and vinyl floors, Cabot's Laminate Floor Polish delivers visible results you can trust.



Features and Benefits

- Restores shine
- Reduces the appearance of scratches and marks
- Fast and easy to use
- Prolongs the life of coated surfaces
- Does not damage existing coatings
- Safe for laminate surfaces

Uses

For use on sealed laminate, vinyl, linoleum, cork flooring, polished concrete, slate and ceramic tiles.

Precautions and Limitations

Ensure the surface is clean and dry, and avoid use on unsealed or non-recommended flooring types
Do not apply product if temperature is below 10 degrees or above 30 degrees or is likely to reach these temperatures during the drying period. Equally, relative humidity should not exceed 85%.

Performance Guide

Weather **Not applicable**	Heat Resistance **Not applicable**
Water **Not applicable**	Abrasion **Not applicable**

Typical Properties

Gloss Level **No applicable**	Heat Thinner **Not applicable**
Colour **Milky white in appearance and dries clear**	
Components **1 pack**	Number of Coats **1**
Toxicity **Not applicable**	
Touch Dry **1 hour**	
Clean Up **Water**	
Application Methods **Pad** Mop sponge	

Application Conditions

	Min	Max	Recommended
Recoat Time (min/hours)			1 hour
Theoretical Spread Rate (m²/L)			60

Typical Property Notes
Coverage: Up to 60m2/L.
Drying times: All timings quoted at 25°C and 50% humidity. Cooler or humid conditions may require longer drying times.
Recoat: 1 hour.
Walk on: 4 hours.
Replace furniture after 48 hours.

Application Guide

Surface Preparation

Ensure the surface is thoroughly cleaned with Cabot's Wood Floor Cleaner prior to application of Cabot's Laminate Floor Polish (following label directions). Cabot's Wood Floor Cleaner will remove dirt and dust to allow Laminate Floor Polish to properly adhere to the surface. Allow the surface to dry fully before applying Cabot's Laminate Floor Polish.

Application Procedure and Equipment

Important: Do NOT shake before use to minimise bubbles forming.
1. Apply 1 coat of Cabot's Laminate Floor Polish with a sponge mop or Cabot's lambswool applicator. Do not allow pools of liquid to form on the surface.
2. If required, apply 1 further coat following the same application method as above. Additional coats will increase gloss level and durability.
3. Allow the product to dry for a minimum of four hours before walking on the surface.

Health and Safety

SDS Number	SDS Link
DLXGHSEN004815	**View SDS Link**

Using Safety Precautions
Risk: Harmful in contact with skin and if swallowed. Irritating to eyes.
Keep out of reach of children.
Read carefully and follow all instructions.
Wash hands, face and all exposed skin thoroughly after handling. Wear protective gloves/protective clothing protective clothing, gloves, eye/face protection and suitable respirator.

If medical advice is needed, have product container or label at hand.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
57MW0557

Size:	Weight:
1L	**1.140 Kg**

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.