

AUIN00005 Intergrain Woodblend Putty

Introduction

Part A
927-line

Description and Image

Intergrain Woodblend is a water based timber and grain filler, suitable for both interior and exterior use. Woodblend has excellent durability, minimal shrinkage and low odour. It is easy to apply and sands to an extremely fine, smooth finish. Woodblend is suitable for use on all timber species and can be coated with water or oil based paints, stains and timber finishes. Woodblend is available in a range of popular timber colours which can be mixed to achieve custom shades.

Environmentally Responsible

Being water based, Woodblend emits significantly less VOC's (volatile organic compounds) into the atmosphere than traditional oil based putties. So, combined with being healthier to use, Woodblend is much gentler on the environment.

Features and Benefits


- Waterbased
- Interior & exterior use
- A range of intermixable colours
- Sets firmly
- Environmentally friendly
- Versatile
- Can match most timber colours
- Does not shrink or crack

Uses

Use on all interior and exterior timber surfaces including weatherboards, decking, flooring and furniture. Woodblend can be used to fill nail holes, splits, knot holes and as a grain filler to give a smooth finish to timber surfaces.

Performance Guide

Weather
Interior and exterior use

Typical Properties			
Heat Thinner Water			
Colour 6 packaged colours			
Components 1		Number of Coats N/A	
Toxicity Lead free.		V.O.C. Level < 110g/L	
Shelf Life Indefinite			
Clean Up  Water			
Clean Up Description Indefinite.			
Application Methods Putty knife			
Application Conditions			
	Min	Max	Recommended
Recoat Time (min/hours)	<input type="text" value="2 hours"/>	<input type="text"/>	<input type="text"/>
Typical Property Notes Drying and re-coat time All timings quoted at 25C and 50% humidity. Drying and overcoating times will be retarded by cold or humid conditions. Deep holes may require longer.			

Application Guide
Surface Preparation Surface must be in sound condition, clean, dry and free from dust, grease, wax and oil. Indentations and holes must be clear of all loose material.
Application Procedure and Equipment Apply Woodblend with a flexible filling blade or knife. Fill deep holes in approx. 10mm stages, allowing 2 hours drying time between each stage. To ease application, dampen blade with water. Wipe off excess with a slightly damp sponge. When dry, sand to a smooth finish. When using clear finishes, apply Woodblend after the first coat of clear to minimise smudging. For use as a grain filler, thin Woodblend with 5-10% water to achieve required consistency. Apply with a flexible filling blade or knife and allow to dry. When dry, sand back to bare timber, leaving filler only in the grain. Important Keep container tightly closed when not in use.

Health and Safety	
SDS Number 14272813	SDS Link View SDS Link
Using Safety Precautions Provide adequate ventilation. If using inside keep windows and doors open during use and while drying.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage	
Pack A 927-line	
Size: <input type="text" value="800 gm 100 gm"/>	Weight: <input type="text" value="800 gm 100 gm"/>
Please refer to the Safety Data Sheet for full safety, health and transportation information.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.