

AUCA00346 Cabot's Interior Clean & Care Wipes

Introduction

Part A
N9400097

Description and Image

Cabot's Interior Clean & Care Wipes are specially formulated with a blend of oil and wax to both clean and nourish interior wood surfaces. Unlike standard cleaning wipes, these are designed to be kind on wood, ensuring a streak free finish*, and your timber looks rejuvenated and naturally beautiful every day.

*When used in accordance with label instructions



Features and Benefits

- Fast and easy to use
- Contains oil and wax to both clean and nourish
- Safe for wood
- Does not damage existing coatings
- Streak free finish*

Uses

For use on all sealed and un-sealed wood benchtops, dining tables and furniture.

Precautions and Limitations

For use only on sealed or coated timber surfaces. Not suitable for bare, greyed, or weathered wood. Do not use on freshly coated timber within 2 weeks of application.

Performance Guide

Weather Not Applicable	Heat Resistance Not Applicable
Water Not Applicable	Abrasion Not Applicable

Typical Properties

Colour
White wipes

Components
1 pack

Clean Up
 **Water**

Application Methods
Wipes

Application Guide

Surface Preparation
No surface preparation required. Use the Interior Clean & Care Wipes to clean your interior timber.

Application Procedure and Equipment
1. Open the resealable lid, peel back the sticker slowly and pull out wipes one at a time.
2. Re-seal pack immediately after use to prevent the wipes from drying out
3. Wipe off dust, dirt and grime until clean
4. Dispose of the wipe in the rubbish bin.
NOTE: Excessive dirt or grime may require the use of more than one wipe. For stubborn stains, use Cabot's Everyday Care Wood Surface Cleaner.

Health and Safety

SDS Number
DLXGHCEN004826

SDS Link
[View SDS Link](#)

Using Safety Precautions
May cause an allergic skin reaction.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
N9400097

Size:	Weight:
<input type="text" value="20 pcs"/>	<input type="text" value="308G"/>

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.