

AUDU00160 Dulux Enviro2 Interior Matt

Introduction

Part A
59M Line

Description and Image

Dulux Enviro2 Interior Matt is a very low VOC, low odour premium water based paint. It produces a washable, stain resistance and hard wearing finish suitable for all interior living areas. It contains mould protection to help prevent mould growth.



Features and Benefits

- Water based premium acrylic paint
- Produces a hard wearing finish
- Washable and stain resistant
- Very low VOC <1g/L <https://www.globalgreentag.com/products/enviro2-interior-matt-white/>
- Low odour
- Helps prevent mould growth

Standards And Certifications

<p>Australasia Environmental Product Declaration</p>	<p>Global Green Tag Certified: GreenRate Level A</p>	<p>Global Green Tag Health Rate: Platinum Health</p>	<p>Can contribute towards satisfying Green Star Credits</p>	<p>Can contribute towards satisfying WELL Points</p>

Standards and Certifications

For details on these standards and certifications please reference the 'Approvals' section at the beginning of this document. Please contact your DuluxGroup representative for specific information on ESD credits / points.

Uses

Suitable for all interior living areas and Green Star, Well, LBC building projects.

✓ Interior

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not use at temperatures below 10C, or when the temperature of the surface may fall below 10C during the drying period. Although the film is dry to touch in 30 minutes allow 7 days for film to fully cure before washing.

Tinted Colours

Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use. Darker colours will show more signs of marking and scuffing than lighter colours - if you are considering using a dark colour in a high traffic area you may want to consider a higher sheen level or the use of a protective clear coat.

Performance Guide

Weather

Designed for interior use only. Not recommended for exterior use.

Heat Resistance

Softens and sticks to other painted surfaces over 70°C

Water

Suitable for use in wet areas

Solvent

Sensitive to aromatic hydrocarbons and alcohols

Typical Properties

Gloss Level

3-6 at 60°, 3-7 at 85°

Thinner

Water

Colour

White, may be tinted up to 56ml (2Y) per litre.

Components

1

Number of Coats

2

Toxicity

Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.

V.O.C. Level

<1g/L inclusive of Dulux Low VOC tinter

Meets GBCA V.O.C. Requirements?

Yes

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.

Touch Dry

30 Minutes

Clean Up



Water

Clean Up Description

Clean all equipment with water

Application Methods

- Air Spray
- Airless Spray
- Brush
- Roller

Application Conditions	Solids by Volume		
	<input type="text" value="40"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="62.5"/>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="25"/>
Recoat Time (min/hours)	<input type="text"/>	<input type="text"/>	<input type="text" value="2 Hours"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="16"/>

Application Guide

Surface Preparation

All surfaces must be prepared in accordance with proper trade practices and must be clean and free from dust, dirt, grease and oil. previously painted surfaces, except asbestos cement, must be sanded to remove loose, peeling, flaking or chalky paint. Spot prime bare areas.

Note: To avoid dust from asbestos cement sheeting do not sand or scrub. Wash with bleach solution or appropriate de-mossing chemical where necessary. Wash down.

Application Procedure and Equipment

Brush, roller, spray

Stir well before use with a broad, flat paddle using an up and down scooping action. Apply 2 coats of Dulux EnvirO2 Interior Matt. Thin with up to 100ml of water per litre if necessary.

Health and Safety

SDS Number DLXGHCEN003518	SDS Link View SDS Link
Personal Equipment Wear eye protection	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage

Pack A 59M84179	
Size: <input type="text" value="15 Litre"/>	Weight: <input type="text" value="21.3Kg"/>
Flash Point NA	UN Number NA
Dangerous Goods Class NA	Package Group NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.