AUDU00027 Dulux Envirosolutions Waste Paint Hardener

Introduction

Part A
N5609144

Approvals
N/A

Description and Image

Dulux Envirosolutions Waste Paint Hardener turns unwanted water based paints and water based timber coatings into Non-Hazardous solid waste for easy/convenient hard waste disposal. Dulux Envirosolutions Waste Paint Hardener is sold in 2 pack sizes (25g and 500g).
The 25g pack size will harden 500ml of paint.
The 500g pack size will harden 10L of paint.

Features and Benefits

- Fast, easy and responsible way to dispose of unwanted paint
- No Mess
- Convenient paint disposal method where local council paint collection centres are not present or too far away for drop-off

Uses

Dulux Envirosolutions Waste Paint Hardener is used to dispose of unwanted water based paint waste for both retail (DIY) and trade applications.

Precautions and Limitations

Refer MSDS.
Note 1. Hardener is classified as a hazardous substance according to the criteria of ASCC.
Note 2. Once Hardener is added in proscribed mix quantity as per directions the the hardened paint residue is classified as non-hazardous.

Performance Guide

Weather **N/A**	Salt **N/A**
Heat Resistance **N/A**	Water **N/A**
Solvent **N/A**	Abrasion **N/A**
Acid **N/A**	Alkali **N/A**

Typical Properties

Gloss Level **N/A**	Thinner **N/A**
Colour **Off-White Powder**	
Components **1**	Number of Coats **N/A**
Toxicity **Hazardous. Observe MSDS protocols. Non-Hazardous once reacted with paint.**	
Shelf Life **N/A**	
Sanding Properties **N/A**	Mixing Ratio **N/A**
Touch Dry **N/A**	
Clean Up Description N/A	

Application Conditions

Solids by Volume: 100

	Min	Max	Recommended
Wet Film Per Coat (microns)	0	0	0
Dry Film Per Coat (microns)	0	0	0
Theoretical Spread Rate (m^2/L)	0	0	0

Application Guide

Surface Preparation

N/A

Application Procedure and Equipment

Dulux Envirosolutions Paint Hardener concept has been presented to the EPA and concept/disposal mechanism approved. EPA has indicated that the hardened paint does not have to be classifed as Prescribed Industrial Waste.
25g Dulux Envirosolutions Paint Hardener sachet hardens 500ml of water based paint.
500g Dulux Envirosolutions Paint Hardener sachet hardens 10L of water based paint.

The 500g pack contains a measuring cap fixed underneath the screw cap. One scoop of the measuring cap will harden 250ml of paint.
Once paint hardener has been added stir until into the paint until the paint solidifies. Leave for 2 hours with the lid off. Then remove the hardened paint from the can, wrap in newspaper and dispose of as hard waste (Trade) or via domestic rubbish collection (Retail).

Health and Safety	
SDS Number **22029**	SDS Link **View SDS Link**
Using Safety Precautions Avoid skin and eye contact and breathing in dust. Avoid handling which leads to dust formation.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage
Pack A **N5609144**

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.