

AUHA00013 Hadrian Contractor Ceiling Flat

Introduction

Part A
071-88204

Description and Image

HADRIAN® CONTRACTOR Ceiling Flat is a quick drying, interior latex paint which is specially formulated with a dead flat finish that minimises the appearance of any surface imperfections, making it ideal for ceilings with high levels of critical lighting.

Features and Benefits

- Water based
- Excellent coverage
- Dead flat finish
- Ideal airless spray
- Same day recoat, easy clean up and low odour.
- Saves application time as 2 coat hiding allows quick application.
- Hides plastering faults, ideal for low ceilings and high side light.
- Saves application time on large ceilings.

Uses






HADRIAN® CONTRACTOR Ceiling Flat has a dead flat finish that minimises the appearance of any surface imperfections, making it ideal for ceilings with high levels of critical lighting.

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.
Avoid exposure to steam and condensation for 48 hours after application.
Do not apply at temperatures below 10°C or when the temperature of surface may fall below 10°C during the drying period. Under extremely hot conditions up to 100ml per litre of water may be added to help application.

Performance Guide

Weather Not suitable for exterior use.	Salt NA
Heat Resistance Up to 70C.	Water Not water resistant. Clean surface with damp sponge only.
Solvent Sensitive to aromatic hydrocarbons, alcohols and ketones.	Abrasion Not abrasion resistant.
Acid NA	Alkali NA

Typical Properties			
Gloss Level 0-1 at 60 degrees.		Thinner Water	
Colour Can be tinted to a range of light pastel colours.			
Components 1			
Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.		V.O.C. Level < 25g/L untinted	
Touch Dry 30 Minutes			
Clean Up  Water			
Clean Up Description Wash all equipment with water after use.			
Application Methods  Air Spray  Airless Spray  Brush  Roller			
Application Conditions		Solids by Volume	
		<input type="text" value="28"/>	
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="67.8571"/>	<input type="text" value="67.8571"/>	<input type="text" value="67.8571"/>
Dry Film Per Coat (microns)	<input type="text" value="19"/>	<input type="text" value="19"/>	<input type="text" value="19"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="14.7"/>	<input type="text" value="14.7"/>	<input type="text" value="14.7"/>

Application Guide
<p>Surface Preparation</p> <p>All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Refer to Systems Guide for correct primer, sealer or undercoat required.</p>
<p>Application Procedure and Equipment</p> <p>Brush, roller, conventional or airless spray. Stir thoroughly with a broad flat stirrer, using an upward lifting action. Apply two full coats. Brush/Roller: Apply straight from the can. Use a medium to long nap roller. Avoid excessive brushing or rolling back into paint which has been drying some minutes. On very porous dry surfaces, add up to 100ml water per litre to the first coat only. Airless/Conventional Spray: Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.</p>

Health and Safety	
SDS Number 10427, 0	SDS Link
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage	
Pack A 071-88204	
Size: 15 Litre	Weight: 21.0 Kg
Flash Point NA	UN Number NA
Dangerous Goods Class NA	Package Group NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.