

AUIN00042 Intergrain UltraPrep Mould Killer

Introduction

Part A
552W0337

Description and Image

Intergrain UltraPrep Mould Killer is a biodegradable, environmentally responsible formula with an active mould killing life of 6 hours once diluted. Specially formulated to effectively remove mould from exterior timber including coated and uncoated surfaces.

Note: Lack of visible growth does not necessarily indicate an uncontaminated surface. Many spores are not visible to the naked eye and can germinate and grow beneath surface coatings and timber stains. It is recommended to always use Intergrain UltraPrep Mould Killer in humid and mould susceptible areas as the first step of preparing timber for coating.



Features and Benefits

- Free from hypochlorite bleach
- Specially formulated for use on timber

Uses

On all exterior timber that may be susceptible to, or already contaminated by mould.

Precautions and Limitations

Once powder has been diluted, use within 6 hours.

Typical Properties

V.O.C. Level

0g/L

Meets GBCA V.O.C. Requirements?

Yes

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tint required for non-factory packaged colours.

Clean Up



Water

Application Methods

Stiff bristle brush or broom

Typical Property Notes

Mix ratio

100g/L of water

Coverage

Up to 20m²/800g when mixed

Application Guide

Surface Preparation

Sweep surface to remove loose material such as dirt, leaves, etc.

Application Procedure and Equipment

Mix 800g of Intergrain UltraPrep Mould Killer into 8L of water, stir until powder is fully dissolved. Warm water will help dissolve the powder faster. Scrub on to entire area with a stiff bristle brush.

Leave for 15 minutes, do not allow to dry on the timber, add more product if required to keep it wet.

Rinse off exterior surfaces thoroughly using maximum pressure from a garden hose or use a high pressure water cleaner. For best results, a high pressure water cleaner is recommended.

If any visible mould remains, repeat the process.

Important: Once powder has been diluted, use within 6 hours. Any left over solution can be safely disposed of down a drain.

Health and Safety

SDS Number

DLXGHSEN003394

SDS Link

[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. Read label before use. Wash hands, face and all exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective clothing, gloves, eye/face protection and suitable respirator. Liquid is slippery when spilt.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage	
Pack A 552W0337	
Size: <input type="text" value="800g"/>	Weight: <input type="text" value="878g"/>
Please refer to the Safety Data Sheet for full safety, health and transportation information.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.