

## AUDU00159 Dulux Enviro2 Interior Low Sheen

### Introduction

Part A  
59L-84179

### Description and Image











**Dulux Enviro2 Interior Low Sheen White** is a very low VOC, low odour premium water based paint. It produces a washable, stain resistance and hard wearing finish suitable for all interior living areas. It contains mould protection to help prevent mould growth.



### Features and Benefits

- Water based premium acrylic paint
- Produces a hard wearing finish
- Washable and stain resistant
- Very low VOC  $< 1\text{g/L}$  <https://www.globalgreentag.com/products/enviro2-interior-low-sheen-white/>
- Low odour
- Helps prevent mould growth

**Standards And Certifications**

 <p>Australian Paint Approval Scheme</p>	 <p>Australasia Environmental Product Declaration</p>	 <p>Global Green Tag Certified: GreenRate Level A</p>	 <p>Global Green Tag Health Rate: Platinum Health</p>	 <p>Can contribute towards satisfying Green Star Credits</p>
 <p>Can contribute towards satisfying LEED Credits</p>	 <p>Can contribute towards satisfying WELL Points</p>	 <p>Can assist in meeting LBC Imperatives</p>	 <p>The Declare Label</p>	 <p>Living Building Challenge (LBC) Red List Free</p>

**Standards and Certifications**

For details on these standards and certifications please reference the 'Approvals' section at the beginning of this document. Please contact your DuluxGroup representative for specific information on ESD credits / points.

**Uses**

Suitable for all interior living areas and Green Star, WELL, LEED, LBC building projects.

✓ Interior

**Precautions and Limitations**

**All preparation and painting must conform to AS2311: The Painting of Buildings.**

Do not use at temperatures below 10°C, or when the temperature of surface may fall below 10°C during the drying period. Not recommended for application at temperatures higher than 28°C. Avoid exposure to steam and condensation for 48 hours after application. Although the film is touch dry in 30 minutes allow 7 days for film to fully cure before washing.

**Cleaning schedule**

After application, allow the surface to dry for 7 days prior to cleaning. Do not scrub the surface, use abrasive cleaners or solvent. The surface should be wiped down with a soft damp cloth using mild detergent such as Spray & Wipe or similar.

**Darker colours** will show more signs of marking and scuffing than lighter colours - if you are considering using a dark colour in a high traffic area you may want to consider a higher sheen level or the use of a protective clear coat.



Theoretical Spread Rate (m <sup>2</sup> /L)			16
---	--	--	----

**Application Guide**

Surface Preparation

All surfaces must be prepared in accordance with proper trade practices and must be clean and free from dust, dirt, grease and oil.

**Previously painted surfaces**, except asbestos cement, must be sanded to remove loose, peeling, flaking or chalky paint. Spot prime bare areas.

**Note:** To avoid dust from asbestos cement sheeting do not sand or scrub. Wash with bleach solution or appropriate de-mossing chemical where necessary. Wash down.

Application Procedure and Equipment

**Brush, roller, spray**

Stir well before use with a broad, flat paddle using an up and down scooping action. Apply 2 coats of Dulux EnvirO2 Interior Low Sheen. Thin with up to 100ml of water per litre if necessary.

**Health and Safety**

SDS Number <b>DLXGHCEN003519</b>	SDS Link <a href="#">View SDS Link</a>
Personal Equipment <b>Wear eye protection</b>	
<b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b>	

**Transport and Storage**

Pack A <b>59L84179</b>	
Size: <b>4 Litre 10 Litre 15 Litre</b>	Weight: <b>6.0 Kg 14.8 Kg 21.9 Kg</b>
Flash Point <b>NA</b>	UN Number <b>NA</b>
Dangerous Goods Class <b>NA</b>	Package Group <b>NA</b>

**Further Information**

**Dulux EnvirO2 Certification Documents**

#### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.