

AUCM00008 Dulux Creativo Microcement Fondo Part A & Part B

Introduction

Part A
Fondo 194X2537-7L

Part B
Microcemento 194X2535-5KG

Description and Image

Dulux Creativo Microcement Fondo Part A has to be mixed with Dulux Creativo Microcemento Part B

(ratio 2:1 by weight or 7L : 5 kg) before application.

It is designed to be used as a base coat, but can also be used as a finishing one in case a highly textured design wants to be achieved. In this case, Dulux Creativo Fondo can be coloured with Dulux tinters to our dedicated Microcement colour range.



Features and Benefits



- Suitable for interior and exterior

Uses

Dulux Creativo Microcement Fondo Part A & Part B is part of the overall system to create seamless luxury surfaces with an innovative design.

It is highly suitable for the finishing of vertical walls and horizontal floorings, both indoor and outdoor such as:

Floorings and walls for residential or industrial use, medical environments, food rooms, retails, shop floors, showrooms, bathroom, shower rooms, sinks and bath tubs, and floors with radiant heating.

Typical Properties			
V.O.C. Content 19 g/l			
Clean Up  Water			
Application Methods  Trowel			
Specifications	Solids by Volume <input type="text" value="56"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="889"/>	<input type="text" value="963"/>	<input type="text" value="926"/>
Dry Film Per Coat (microns)	<input type="text" value="499"/>	<input type="text" value="541"/>	<input type="text" value="520"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="1.12"/>	<input type="text" value="1.04"/>	<input type="text" value="1.08"/>
Drying Time	Min	Max	Recommended
Recoat Time (min/hours)	<input type="text" value="8 hours"/>	<input type="text"/>	<input type="text"/>
Full Cure	<input type="text" value="7"/>		
Comments	<input type="text" value="Pot-life of product mix is 1 hour, do not use it after this time."/>		

Application Guide
<p>Surface Preparation</p> <p>Surfaces need to be compact, sound, dry, solid, clean, free from dust, grease, oil, waxes, sealers, silicone compounds or any other item that might affect adhesion of the system. Old paint and filming agents, not perfectly compact and adherent to the substrate, needs to be removed</p>
<p>Application Procedure and Equipment</p> <p>Mix well Creativo Fondo Part A with Creativo Microcemento with a mixing drill for minimum 5 minutes or until a smooth, lump free, homogeneous mix is achieved. Leave the mix to settle a few minutes and proceed with application. Pot life of the two components, once mixed, is 1 hour, don't use the mixture after this time, don't try to re-activate it by adding water as the cement curing process has already started. Mix only the material that will be used. Apply the product by stainless steel spatula trying to avoid very thick layers per single coat. After at least 8 hours sand manually or by sanding machine any imperfection, using 60G sandpaper and vacuum the dust, wear suitable respirator. When dealing with very big areas, include fibre mesh, 80-90 gr/m², trowelling into the first coat. We recommend the use of shoe covers during all the operations to avoid dirtying the surfaces. Avoid wetting the surface before completing the system, stains or spots will affect the final result.</p>

Health and Safety	
SDS Number DLX004037	SDS Link View SDS Link
<p>Using Safety Precautions Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.</p> <p>FIRE: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).</p> <p>SPILLS & LEAKS: Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. Refer to State/Territory Land Waste Management Authority for disposal.</p> <p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p>INHALED: Remove from contaminated area. Seek medical advice.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
Line Shade /Pack A 194X2537-7L	
Size: <input type="text" value="7L"/>	Weight: <input type="text" value="11 kg"/>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.