

AUPR00046 Dulux Professional Hot Weather Thinner

Introduction

Part A
920-89933

Description and Image

Dulux Professional Hot Weather Thinner eases application of water based paints in hot, dry or windy conditions or when such paints are applied over dry porous surfaces.

Features and Benefits

- Slows drying
- Maintains a wet edge to overcome brush drag, improves lapping

Uses

As an additive for easing application of water based acrylic paints under exceptionally fast drying conditions - high temperatures, low humidity, dry porous surfaces or wind. It is useful for both exterior and interior paints.

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

50 ml per litre for all but the most severe conditions. Up to 100 ml may be used if necessary. This product works by slowing the drying process. Do not add under cool conditions (below 15C), when air circulation is poor or when the relative humidity is high.

Performance Guide


Weather
NA

Heat Resistance
NA;

Water
NA

Solvent
NA

Abrasion
NA

Typical Properties			
Thinner DO NOT THIN			
Colour A water white liquid.			
Components 1		Number of Coats N/A	
Toxicity No toxic residues on drying. See also Health & Safety Section.		V.O.C. Level 1040	
Sanding Properties N/A		Mixing Ratio N/A	
Touch Dry N/A			
Clean Up  Water			
Clean Up Description Thoroughly wash brushes in water before re-using.			
Application Conditions		Solids by Volume	
		<input type="text" value="0"/>	
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="0"/>	<input type="text"/>	<input type="text" value="0"/>
Dry Film Per Coat (microns)	<input type="text" value="0"/>	<input type="text" value="0"/>	<input type="text" value="0"/>
Recoat Time (min/hours)	<input type="text" value="NA"/>	<input type="text"/>	<input type="text"/>

Application Guide
Application Procedure and Equipment Not Applicable

Health and Safety	
SDS Number 21757	SDS Link View SDS Link
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage	
Pack A 920-89933	
Size: <input type="text" value="1 Litre"/>	Weight: <input type="text" value="1.2 Kg"/>
Flash Point NA	UN Number NA
Dangerous Goods Class C1	Package Group MA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.