

AUDU00125 Dulux Ceiling White Flat

Introduction

Part A
615-D0115

Approvals
APAS 0260/5

Description and Image

Dulux Ceiling White provides a flat finish with excellent hiding power, ideal for use on ceilings. The flat finish minimises reflection and therefore reduces the appearance of surface imperfections. Dulux Ceiling White is a low VOC and low odour water based paint.



Features and Benefits

- Flat finish
- Excellent hiding power
- 5 year anti-mould guarantee
- Low spatter formula
- Low odour & low VOC
- Tintable to light colours
- Water based
- Flat finish helps hide imperfections
- 2 hour recoat
- Easy clean up and low odour
- Easy to apply
- Water wash up

Uses

Dulux Ceiling White is a low VOC interior tintable water based flat with excellent hiding power for use on ceilings.

✓ **Interior**

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not exceed recommended spreading rate. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 20 minutes, allow 7 days for the film to fully cure before lightly cleaning with a sponge wet with mild detergent solution. Do not paint at temperatures below 10 degrees Celsius or when the temperature of surface may fall below 10 degrees Celsius during the drying period.

| Performance Guide | |
|---|---|
| Weather Not suitable for exterior applications. | Salt NA |
| Heat Resistance Up to 60°C. | Water For interior use in damp and dry areas. |
| Solvent Poor solvent resistance, sensitive to aromatic hydrocarbons and alcohols. | Abrasion N/A |
| Acid NA | Alkali NA |

| Typical Properties | | | | | | | | | |
|---|--|-------------------------|-----------------------|-----|-------------|---|--|--|-----------|
| Gloss Level <2.0 at 60° | | | | | | | | | |
| Colour White base, tintable to lighter colours. | | | | | | | | | |
| Components 1 | Number of Coats 2 | | | | | | | | |
| Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3. | V.O.C. Level <14g/L tinted and untinted | | | | | | | | |
| Meets GBCA V.O.C. Requirements? Yes | Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours. | | | | | | | | |
| Touch Dry 30 minutes (25°C, 50% RH) | | | | | | | | | |
| Clean Up |  Water | | | | | | | | |
| Application Methods |  Air Spray  Airless Spray  Brush  Roller | | | | | | | | |
| Application Conditions | <p>Solids by Volume 27.6</p> <table> <tr> <td>Recoat Time (min/hours)</td> <td>Min 2 Hours</td> <td>Max</td> <td>Recommended</td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td>16</td> </tr> </table> | Recoat Time (min/hours) | Min 2 Hours | Max | Recommended | Theoretical Spread Rate (m ² /L) | | | 16 |
| Recoat Time (min/hours) | Min 2 Hours | Max | Recommended | | | | | | |
| Theoretical Spread Rate (m ² /L) | | | 16 | | | | | | |

Application Guide

Surface Preparation

Previously Painted:

Dust, then clean with Selleys Sugar Soap. If the surface is glossy, lightly sand back to a dull finish. Spot prime repairs with Dulux 1 Step Acrylic Primer Sealer Undercoat and then apply a full coat over the entire surface.

Unpainted Plasterboard:

Apply a coat of Dulux 1 Step Acrylic Sealer Undercoat over the entire surface.

Application Procedure and Equipment

Stir well before use with a broad flat paddle using an up and down scooping action. Apply two coats of Dulux Ceiling White ensuring that the first coat is completely dry before applying the second. Remember, using poor quality or worn rollers can effect the final finish achieved. Note: some colours may require more than two coats, especially when painting over dark colours.

Health and Safety

SDS Number
DLXINTEN000959

SDS Link
[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

When applying Patina Green wear rubber gloves and safety goggles.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
615D0115

Size: **1L; 2L; 4L; 10L; 15L** Weight: **1.340kg, 2.680kg, 5.360kg, 13.40kg.**

| | |
|------------------------------------|----------------------------|
| Flash Point NA | UN Number NA |
| Dangerous Goods Class NA | Package Group NA |

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.