

AUPP00019 Porter's Paints Universal Primer

Introduction

Part A
PZ5-D0850

Description and Image

A tough all-purpose primer for use when extra masking or isolation of substrate is required, such as over oil-based (enamel) paints when changing to a water-based (acrylic) system, or for timber prone to tannin bleed. Particularly suitable for use over galvanised iron.

Features and Benefits

- Especially suited to use under Porter's Liquid Silver, Porter's Liquid Stainless Steel and Porter's High Gloss Acrylic for a smoother result.
- Water wash-up
- Use over oil based coatings when changing to a waterbased (acrylic) paint system
- Interior/Exterior

Uses

Interior and exterior. Can be applied to most suitably prepared interior or exterior surfaces, including timber, masonry, plaster board, set plaster, timber and furniture.

Precautions and Limitations

Not suitable for use over non-ferous metals such as unpainted stainless steel, brass, copper or bare aluminium.
Does not inhibit rust. Not suitable for use over previously oiled timbers. Universal Primer gives a very smooth finished result, and subsequently is not suitable for use under a number of Porter's products (that require a rougher, more absorbent undercoat) such as Milk Paint, Lime Wash, Interno, Boncote Cement Paint, Distemper and Fresco.
Do not apply in high humidity, below 10°C or above 30°C.

Typical Properties

Thinner
Water

Colour
White

Components
1

Number of Coats
1 or 2

V.O.C. Level
< 33g/L

Touch Dry
2 hours

Clean Up
 **Water**

Clean Up Description
Clean brushes and equipment with water. Do not pour paint down the drain. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Please confirm local requirements. For more information on responsible disposal of paint and packaging visit paintback.com.au or painttakeback.co.nz

Application Methods

 **Brush**  **Roller**

Application Conditions

Solids by Volume

41

	Min	Max	Recommended
Wet Film Per Coat (microns)			100
Dry Film Per Coat (microns)			41
Recoat Time (min/hours)	6 hours	indefinite	6 hours
Theoretical Spread Rate (m ² /L)			10

Application Guide

Surface Preparation

ON NEW UNPAINTED FRESH SET PLASTER:

Do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

OVER PREVIOUSLY PAINTED SURFACES:

Scrape off loose and flaking paint. Fill nail holes and cracks with suitable filler, sand and dust off. If previous paint is a gloss or semi-gloss finish, lightly sand entire surface to abrade and provide a "key" for the primer. Spot prime all joints and repaired areas.

ON UNPAINTED TIMBER PRONE TO TANNIN BLEED:

Ensure surface is clean and sanded. Wipe with a damp cloth to remove any dust. Apply 1 coat of Porter's Tannin Check. Allow to dry 2 hours before applying 1 or 2 coats of Porter's Universal Primer.

OVER METAL OR WEATHERED GALVANISED IRON:

Use a wire brush to remove any loose or flaking paint or any unstable rust, rinse well with water and allow to dry. Universal Primer does not inhibit rust, so the application of an anti-corrosive metal primer or a rust converter may be advisable.

New galvanised iron is supplied with an oil film on it which is normally left to weather before painting. If immediate painting is required the oil must be removed. Use an alkaline degreaser or clean surface thoroughly using hot water, sugar soap and a scouring pad. Rinse well and allow to completely dry.

Porter's Universal Primer is recommended for use as a primer/undercoat prior to the application of Porter's Alchemy Liquid Silver.

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

Application Procedure and Equipment

Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point.

Do not apply if the surface temperature is greater than 30°C or below 10°C, or likely to fall below 10°C during the application or drying period.

Stir thoroughly prior to use. Apply one or two coats by brush or medium nap roller. On bare timber spot prime all knots prior to application. Touch dry in 2 hours. Allow minimum 6 hours dry time between coats. Allow 24 hours dry time before over-coating. Porter's Universal Primer will reach maximum cure and hardening up to a week after painting.

Health and Safety

SDS Number

DLXGHSEN001343

SDS Link

[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. . Use only in well ventilated areas.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

PZ5-D0850

Size:

500ml, 1 litre & 4 litre

Weight:

740g, 1.43 Kg, 5.52 Kg

Flash Point

NA

UN Number

NA

Dangerous Goods Class

Not classified as Dangerous Goods for transport by Road & Rail and Marine, Not classified as Dangerous Goods for transport by Air.

Package Group

NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.