

AUPR00043 Dulux Professional Acousticoat Flat

Introduction

Part A
56AD0120

Description and Image

Dulux Professional Acousticoat Ceiling Tile Paint is a flat acrylic ceiling paint designed specifically to help refresh aged acoustic ceiling tiles. It has been specially formulated to help ensure that paint will not stick tiles to the grid system, so it can be applied to grids and tile simultaneously. This product contains mould inhibitors to help prevent the growth of mould.

All Dulux Professional products are designed to meet the application needs of painters.

Features and Benefits

- Low Odour, Low VOC
- Refreshes Acoustic Ceiling Tiles
- Does not impact acoustic performance
- Refresh tired looking ceilings
- Minimise replacement costs
- Fast return to service of ceilings

Uses

Dulux Professional Acousticoat Ceiling Tile Paint has been designed specifically for use on ceiling tiles. Acousticoat will not impede the acoustic properties of a tiled ceiling. The paint has been formulated such that it will not stick tiles to the grid, meaning tiles and grid can be painted over simultaneously.

✓ **Ceiling**

Precautions and Limitations

Limitations

Not for exterior exposure

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not use at temperatures below 10C, or when the temperature of surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Tinted Colours: Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use.

Performance Guide

Weather

Not suitable for exterior use

Heat Resistance



Up to 70 degrees

Solvent

Sensitive to alcohols and aromatic hydrocarbons.

Abrasion

No suitable for high abrasion areas.

Typical Properties			
Gloss Level <5 units at 85 degrees			
Colour White (can be tinted to a range of colours)			
Components 1		Number of Coats 1	
Toxicity Lead free. Dry film is non-toxic.		V.O.C. Level <5 g/L (Tinted or Untinted)	
Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry 30 minutes			
Clean Up  Water			
Application Methods  Airless Spray			
Application Conditions	Solids by Volume <input type="text" value="19.14"/>		
	Min	Max	Recommended
Recoat Time (min/hours)	<input type="text"/>	<input type="text"/>	<input type="text" value="NA"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="8"/>

Application Guide
<p>Surface Preparation</p> <p>Ensure all surfaces are clean and dry prior to application. Brush to remove dust. If the ceiling tiles appear damaged and unsuitable for paint application, the affected tiles should be replaced. Seal all stains prior to paint application with Dulux Precision Ceiling Stain Blocker.</p>
<p>Application Procedure and Equipment</p> <p>Dulux Professional Acousticoat Ceiling Tile Paint has been developed for spray application only. Thoroughly stir all products before use to ensure that solids are blended consistently.</p> <p>Thinning : Not Required, product has been designed for spray application.</p> <p>Airless Spray Advice Tip Size: 515 Pressure:1500-2000</p> <p>Mask up any ceiling features such as lighting fixtures and fire sprinklers, then spray the entire ceiling (tiles and grid) with a light coating of Dulux Professional Acousticoat Ceiling Tile Paint as per directions.</p>

Health and Safety	
<p>SDS Number DLXGHSEN002957</p>	<p>SDS Link View SDS Link</p>
<p>Using Safety Precautions Keep out of reach of children.</p> <p>Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
<p>Pack A 56A-D0120</p>	
<p>Size: <input type="text" value="15L"/></p>	<p>Weight: <input type="text" value="20kg"/></p>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.