

AUPR00013 Dulux Professional Quick Dry Undercoat

Introduction

Part A
361-84193

Description and Image

Dulux Professional Quick Dry Undercoat is a same day re-coat interior oil based undercoat with excellent filling and sanding properties for a superfine finish.

Features and Benefits

- Quick drying
- Excellent filling
- Easy superfine sanding
- Saves time; can be recoated the same day.
- Gives smooth finish on open grained timbers including meranti.
- Less time and effort to sand off to give a smooth surface.

Uses

Use Dulux Professional Quick Dry Undercoat as a rapid dry interior undercoat over bare timber, suitably sealed masonry, hardboard, etc. and primed metal. Its sanding and filling properties are excellent, giving a superfine finish for all topcoats.

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.
Do not apply if the surface temperature is below 10C or conditions indicate it will fall below 10C during the drying period.

Performance Guide

Weather

Not recommended for exterior use.

Heat Resistance

Up to 120C. Prolonged exposure to 120C heat will cause embrittlement.

Water






Excellent resistance to condensation and water splash as part of system.

Solvent

Resistant to alcohol & hydrocarbons. Film is liable to attack from strong solvents.

Abrasion

Good when topcoated.

Typical Properties			
Gloss Level Flat		Thinner Mineral Turpentine	
Colour White, may be tinted up to 25ml per litre.			
Components 1			
Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.		V.O.C. Level < 495g/L untinted	
Touch Dry 1 Hour			
Clean Up  Thinner			
Clean Up Description Clean all equipment with mineral turpentine.			
Application Methods  Air Spray  Airless Spray  Brush  Roller			
Application Conditions		Solids by Volume	
		<input type="text" value="42"/>	
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="100"/>	<input type="text" value="100"/>	<input type="text" value="100"/>
Dry Film Per Coat (microns)	<input type="text" value="42"/>	<input type="text" value="42"/>	<input type="text" value="42"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="10"/>	<input type="text" value="10"/>	<input type="text" value="10"/>

Application Guide

Surface Preparation

All surfaces must be thoroughly dry, clean and free of all loose dirt, surface chalk, grease mould, mildew and wax, loose or flaking paint. Sand smooth, dust down, fill and prime in accordance with the requirements of the chosen system.

Application Procedure and Equipment

Brush, roller, conventional or airless spray

Stir thoroughly before and during use.

Brush/Roller

Apply by brush or roller, full even coats direct from the container. If necessary up to 50ml per litre of mineral turpentine may be added to ease application.

Airless/Conventional Spray

Suitable for application by all standard spray equipment. If necessary thin up to 100ml per litre of DULUX Spraying Thinner to aid atomisation.

Health and Safety

SDS Number
36835, 0

SDS Link
[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

361-84193

Size:

Weight:

4 Litre 10 Litre 20 Litre

5.6 Kg 13.8 Kg 21.4 Kg

Flash Point

>23C

UN Number

1263

Dangerous Goods Class

3

Package Group

III

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.