

AUBG00014 Berger Gold Label Ceiling Flat

Introduction

Part A
678-87755

Approvals
APAS 0260/5

Description and Image

Berger Gold Label® Ceiling Flat is an interior acrylic ceiling paint with excellent opacity, adhesion and dead flat sheen level.



Features and Benefits

- Water based
- Excellent opacity
- Dead flat finish
- Same day recoat, easy clean up and low odour.
- Saves application time as two coat hiding allows rapid application.
- Hides plastering imperfections.

Uses

Use Berger Gold Label Ceiling Flat on any plasterboard, plaster or cement sheet ceilings for a flat finish to hide minor surface imperfections under critical lighting conditions.






✓ **Interior**

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not paint at temperatures below 10C or when the temperature of surface may fall below 10C during the drying period. In normal conditions 7 days curing is required to develop full hardness and resistance properties.

Performance Guide	
Weather Not recommended for exterior use.	Salt NA
Heat Resistance Resists up to 70C.	Water Not suitable for use in wet areas.
Solvent Sensitive to hydrocarbons, alcohols, ester, ketones and other strong solvent	Abrasion Moderate resistance to abrasion.
Acid NA	Alkali NA

Typical Properties	
Gloss Level 0-1 at 60 degrees	Thinner Water
Colour Can be tinted to a range of pastel colours.	
Components 1	
Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.	V.O.C. Level < 35g/L untinted
Touch Dry 20 Minutes	
Clean Up  Water	
Clean Up Description Clean all equipment in water.	
Application Methods  Air Spray  Airless Spray  Brush  Roller	
Application Conditions	<div>Solids by Volume</div> <div>25</div> <div> <div>Min</div> <div>Max</div> <div>Recommended</div> </div> <div> <div>Wet Film Per Coat (microns)</div> <div>76</div> <div>76</div> <div>76</div> </div> <div> <div>Dry Film Per Coat (microns)</div> <div>19</div> <div>19</div> <div>19</div> </div> <div> <div>Recoat Time (min/hours)</div> <div>2 Hours</div> <div>Indefinite</div> <div></div> </div> <div> <div>Theoretical Spread Rate (m²/L)</div> <div>13.2</div> <div>13.2</div> <div>14</div> </div>

Application Guide

Surface Preparation

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply sealer or undercoat as required.

Application Procedure and Equipment

Brush, roller, conventional or airless spray

Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action.

Brush/Roller

Rinse brush or roller in water before starting, and use while still slightly damp. Apply two full even coats direct from the container. Under hot conditions or on very absorbent surfaces, up to 100ml of clean water may be added per litre to assist application.

Airless/Conventional Spray

Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.

Health and Safety

SDS Number

10033, 0

SDS Link

[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

678-87755

Size:

Weight:

10 Litre 15 Litre

14.8 Kg 21.4 Kg

Flash Point

NA

UN Number

NA

Dangerous Goods Class

NA

Package Group

NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.