

AUIN00048 Intergrain Colour Additive

Description and Image

Intergrain Colour Additive is a tint concentrate for adding colour to Intergrain Universal™ Timber Oil. Refer to Intergrain Universal Timber Oil instructions for surface preparation and application instructions.



Uses

Adds colour to Intergrain Universal Timber Oil.

Precautions and Limitations

Final colour depends on a number of factors including raw timber colour, porosity and application rate. Always test colour in an inconspicuous area before completing your project.

Typical Properties

Colour

Range of colours

Clean Up

Mineral Turpentine

Clean Up Description

Warning: To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Guide

Surface Preparation

Refer to Intergrain Universal Timber Oil instructions.

Application Procedure and Equipment

Refer to Intergrain Universal Timber Oil instructions.

Addition rate

Add 40ml Colour Additive to 1L of Universal Timber Oil

Add 1 x Colour Additive to 5L of Universal Timber Oil

Add 2 x Colour Additive to 10L of Universal Timber Oil

Health and Safety	
SDS Number DLXGHSEN003789	SDS Link View SDS Link
<p>Using Safety Precautions</p> <p>Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.</p> <p>Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.