

AUDU05800 Dulux Design Light Texture Effect

Introduction

Line Shade
690D0181

Approvals
N/A

Description and Image

Create a subtle textured look with Dulux Light Texture. This combination of a fine grain finish with the soft variation in colour creates a sense of warmth and dimension. Available in a curated range of neural, earthy tones.

Features and Benefits

- Ultra Matt Sheen Level - helps hide surface imperfections
- Water Based and Low VOC for easy clean up and low odour
- UV Resistance - suitable for exterior application
- Self-priming on previously painted surfaces - Easy to use
- Dirt resistant

Uses

✓ Interior ✓ Exterior ✓ Wall

Precautions and Limitations

Do not apply in high humidity, below 10°C or above 30°C.

Do not expose to condensation, steam or high humidity before fully cured.




Surfactant leaching can occur when environmental moisture such as rain, dew or high humidity on exteriors, and steam or condensation on interiors - causes the water-soluble components of newly applied paint to be extracted and deposited on the surface. Surfactant leaching, whilst unsightly, does not affect paint performance or durability. It is more apparent visually with deep and dark colours. Prevention: avoid painting in the later part of the day if humid, cool or damp conditions are expected in the evening or overnight. Allow interior paints to fully cure before subjecting paintwork to steam and condensation.

Can be gently cleaned using a mild soap and soft cloth for interior.

Ensure that paint is thoroughly stirred before use. Check colour before use.

Performance Guide

Weather Good resistance to weathering	Salt N/A
Heat Resistance Softens at temperatures above 70°C	
Solvent Sensitive to aromatic hydrocarbons and alcohols.	Abrasion Good resistance to abrasion.
Acid N/A	Alkali N/A

Typical Properties			
Gloss Level Less than 5 at 60 degrees		Thinner water	
Colour Tintable to a curated range of colours			
Dulux Colour Base ✔ White			
Components 1		Number of Coats 2	
Toxicity Lead free. Dry film is non-toxic.		V.O.C. Level < 5g/L untinted	
Shelf Life N/a			
Pot Life N/A		Touch Dry 1 hour (at 25°C & 50% Relative Humidity)	
Clean Up <div> Water</div>			
Clean Up Description Clean all equipment with water.			
Application Methods <div><div> Brush</div><div> Roller</div></div>			
Application Conditions		Solids by Volume	
		<div>47</div>	
	Min	Max	Recommended
Dry Film Per Coat (microns)	<div>36</div>	<div></div>	<div>36</div>
Recoat Time (min/hours)	<div>2</div>	<div>Indefinite</div>	<div>2</div>
Theoretical Spread Rate (m²/L)	<div>13.06</div>	<div></div>	<div>13.06</div>

Application Guide

Surface Preparation

- Do not apply paint if the temperature is below 10°C or likely to fall below 10°C during the drying period.

All surfaces must be thoroughly cleaned and free of all dirt, dust, grease, loose or flaking paint. Efflorescence or mould on application surfaces must be treated. Occasionally, an apparently sound old paint will lose adhesion when recoated. To avoid this, check the adhesion of the old paint by cutting an 'X' through a clean area of the film with a sharp blade, press cellulose tape firmly across the cut and rip it off. If the old paint comes off with the tape it should be removed before repainting. Flatten glossy surfaces by thoroughly sanding, then wipe clean with a damp cloth.

Only self priming on previous painted surfaces.

Apply primer, sealer or undercoat as required.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely.

Primer is required on unpainted surfaces and spot priming repaired areas.

Application Procedure and Equipment

Do not apply if the surface temperature is greater than 30°C or below 10°C, or likely to fall below 10°C during the application or drying period. Stir thoroughly prior to use.

Apply two coats by brush, or a medium nap roller. Ideally a block brush or 12-15 nap roller.

Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

Health and Safety

SDS Number

DLXGHSEN004470

SDS Link

[View SDS Link](#)

Using Safety Precautions

For detailed information refer to the current Material Safety Data sheet.

Keep out of reach of children.

Use only in well ventilated areas.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

690-D0181

Size:

2L 4L

Weight:

3.4kg, 6.5kg

Flash Point

N/A

UN Number

N/A

Dangerous Goods Class

N/A

Package Group

N/A

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.