AUFW00101 Feast Watson Mastertouch Wipe On Poly Satin

Introduction

Part A
917W0095

Description and Image

Feast Watson Feast Watson Mastertouch Wipe-On Poly is a clear, silky smooth, oil based polyurethane finish that provides durable protection with classic, handrubbed beauty. Mastertouch Wipe-On Poly is easily applied with a cloth, without any drips or brush marks. Mastertouch Wipe-On Poly is suitable for all interior woodwork including furniture, doors and windows, architraves, panelling and trim.
Mastertouch Wipe-On Poly is not suitable for high traffic areas such as floors. For flooring use Feast Watson Floorclear.

Features and Benefits

- Wipe on finish.
- Oil based polyurethane.
- Easy to apply.
- Classic, hand-rubbed beauty.
- Durable protection.
- No drips or brush marks.

Uses

All interior woodwork including furniture, doors and windows, architraves, panelling and trim.

Precautions and Limitations

Mastertouch Wipe-On Poly is not suitable for high traffic areas such as floors.
Soak application cloths in water before disposal.

Performance Guide

Weather **Interior only.**	Heat Resistance **Up to 120C**
Water **Good.**	Abrasion **Not suitable for high traffic areas such as floors.**

Typical Properties

Gloss Level
Satin

Colour
Clear

Components	Number of Coats
1	**2+**

V.O.C. Level
< 570g/L

Meets GBCA V.O.C. Requirements?
No

Touch Dry
2 hours

Clean Up Description
Mineral turpentine
To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Methods

Lint-free cloth.

Application Conditions

Solids by Volume: **26**

	Min	Max	Recommended
Recoat Time (min/hours)	**6 hours**		
Theoretical Spread Rate (m²/L)		**16**	

Typical Property Notes

Drying time
Drying times are given at 25°C and 50% relative humidity.
Lower temperatures or higher humidity can lead to extended drying times.
Touch Dry: 2 hours
Recoat: 6 hours

Coverage
Up to 16m² per litre.

Application Guide

Surface Preparation

Fill nail holes, cracks and other defects with a Water Based Putty after applying the first coat of this product for accurate colour matching.
Remove stains, dirt, wax, grease and oil with mineral turpentine. Remove any polish with a suitable polish remover.

Bare timber
Sand to a smooth surface and remove all sanding dust before coating.
For naturally oily timbers, seal the timber with Feast Watson Proofseal™ as per the directions prior to application.

Previously coated timber
Previously varnished surfaces need to be sanded to a dull finish. Remove all sanding dust before coating.
Thoroughly clean the surface with floor clean and allow to dry.
Apply one coat to a small test area. Allow to dry for 6 hours. Press sticky tape firmly to the surface and pull off quickly. If the coating comes off, sand back to bare timber. If coating adheres well, sand the entire area with 180 - 240 grit paper for good adhesion, remove dust, then follow application instructions.

Application Procedure and Equipment

Shake Mastertouch Wipe-On Poly container for one minute prior to use.

Interior timber
Apply a liberal amount with a clean lint free cloth in the direction of the grain.
Allow to dry for a minimum of 6 hours.
Subsequent coats can be applied as required following instructions above.
A light sand with 240 grit sand paper is recommended between coats.

Staining
Apply Feast Watson Prooftint™ following label directions prior to the application of Mastertouch Wipe-On Poly. Allow Prooftint to dry the recommended period before applying Mastertouch Wipe-On Poly.

Maintenance
Regularly monitor the surface for signs of colour loss or surface defects.
When required, lightly sand the surface and remove dust. Recoat with additional coats of Mastertouch Wipe-On Poly as per application instructions.

Health and Safety

SDS Number	SDS Link
23260	**View SDS Link**

Using Safety Precautions
Keep out of reach of children.
Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. If painting large areas wear an organic vapour respirator. This paint is flammable, so eliminate any sources of ignition. Do not smoke.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
917W0095

Size:	Weight:
1L	**1kg**

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.