

AUDU06192 Dulux Precision Mask & Peel Translucent

Introduction

Part A
51WD0178

Description and Image

Dulux PRECISION Mask & Peel is a low VOC, water based, peelable liquid masking tape for temporary protection of surfaces including glass, stainless steel, laminates, powder coated and smooth non-porous surfaces.

Dulux PRECISION Mask & Peel features Wet-on-Wet technology allowing for a quick recoat time. It also acts as a sealer for bare timber substrates, saving time and labour when masking and cutting in by hand.



Features and Benefits

- Easy to apply & remove
- Temporary protection of non-porous interior & exterior surfaces
- Wet-on-Wet technology
- Acts as a sealer on bare timber substrates

Uses

For interior & exterior surfaces including glass, stainless steel, laminates, powder coated and smooth non-porous surfaces where temporary protection is required.

Suitable for use on multi-pane timber windows and doors for masking purposes during painting. Product will adhere to bare timber or any previously painted surfaces and peel away cleanly from glass.

Previously painted surfaces (including aged enamel or oil based surfaces) must be sanded to remove loose, peeling, flaking or chalky paint. Sand all gloss and semi gloss surfaces to a dull finish and wipe down with a damp cloth to remove surface dust.

All surfaces must be tested prior to application for suitability and expected results.

Suitable for use under Dulux primers and topcoats.

Not suitable for etched, frosted, stained or lead lighted glass & oil-stained timbers.

✓ Interior ✓ Exterior ✓ Doors, Windows & Trim

Precautions and Limitations

All preparation and painting must conform to AS 2311: The Painting of Buildings.

Do not apply if temperature is under 10°C or above 30°C.

Not suitable for application in extreme heat, direct sunlight, or hot drying wind.

Do not use on etched, frosted, stained or lead lighted glass, or acrylic, plastic or Perspex surfaces.

Always spot test surfaces prior to application for suitability of removal and expected results.

The minimum film build required for easy peel off is 90 microns (DFT) for two coats. Ease of peelability is highly dependent on the minimum recommended film build. If the coating is hard to peel off, a third coat may be required.

Performance Guide

Weather

Peelable up to 30 days after external exposure.

Not meant for permanent protection.

Heat Resistance

Up to 70C

Water

Resists splashes, but prolonged contact may soften and remove product.

Solvent

Good for most common chemicals

Abrasion

Medium, Good when top coated

Typical Properties

Thinner

Not required (water)

Colour

Translucent

Components

1

Number of Coats

2

Toxicity

Lead free. Dry film is non-toxic.

V.O.C. Level

<5 g/L

Sanding Properties

Not sandable

Touch Dry

1 hour

Clean Up



Water

Clean Up Description

Water, wash all equipment with clean soapy wash and flush with clean water.

Application Methods



Air Spray



Airless Spray



Brush



Roller

Application Conditions

Solids by Volume

36

Min

Max

Recommended

Wet Film Per Coat (microns)	125	125	125
Dry Film Per Coat (microns)	45	45	45
Recoat Time (min/hours)	1min / 1hr	10min/ inf	1min / 1hr
Theoretical Spread Rate (m ² /L)	8.00	8.00	8.00

Application Guide

Surface Preparation

Do not apply paint if the temperature is below 10°C or above 30°C.

Ensure all surfaces are clean and dry prior to application. Brush down to remove dust. Previously painted surfaces must be sanded to remove loose, peeling, flaking or chalky paint. Sand all gloss and semi gloss surfaces to a dull finish and wipe down with a damp cloth to remove surface dust.

Note: All Surfaces must be tested prior to application for suitability and expected results.

Application Procedure and Equipment

Wet-On-Wet Application

To achieve the desired film build using a 2-coat system, apply the second coat **within 1 to 10 minutes** of applying the first coat. If more than 10 minutes have passed, allow a full **1-hour recoat time** before proceeding with the second coat. Ensure the roller is fully loaded with the product to achieve the required film thickness.

Spray, Brush, & Roller

Thoroughly stir all products with a broad flat stirrer prior to application. Apply two coats of Dulux PRECISION Mask & Peel.

Once dried, test a small area by scoring with a dull blade and peeling a small section. If it does not peel easily, another coat is required for optimal performance.

Spray

Suitable for application by standard spray equipment. Sags and runs can be smoothed with a brush. Do not thin.

Tip size: 0.010-0.015"

Pressure: 1500-1700 psi

Brush

High quality synthetic filament brush (nylon or polyester). Wet brushes with water prior to use to avoid clogging. Apply a full even coat using a premium quality synthetic bristle brush, ensuring the surface is entirely covered. Finish by laying off with light strokes in one direction for a uniform film.

Roller

Use a medium (10-18mm) or long nap (>18mm) synthetic roller to apply a thick, even coat ensuring the entire surface is covered. Lay off with light parallel strokes with a dry roller to achieve a uniform finish.

Dry Time

Allow 2 hours for Mask & Peel to fully dry prior to applying topcoat. Mask & Peel applies white and dries translucent.

Drying times at 25°C and 50% humidity. Under cooler or more humid conditions allow longer. Temperature must be between 10°C and 30°C during application and drying. Avoid exposure to steam and condensation for 48 hours.

Health and Safety	
SDS Number DLX004560	SDS Link View SDS Link
Personal Equipment SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.	
Using Safety Precautions Keep out of reach of children. Provide adequate ventilation. Keep windows and doors open during use and while drying. Avoid contact with skin and eyes or breathing vapour and spray mist (dust). Wash hands after use.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage	
Pack A 51WD0178	
Size: 1L 4L 10L	Weight: 1.197 kg 4.613 kg 11.362 kg
Flash Point Not Applicable - Water Based	UN Number NA
Dangerous Goods Class Not Classified as Dangerous Goods	Package Group NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.