

AUPP00059 Porter's Paints Prepare and Prime Primer

Description and Image

A multi-surface primer and stain blocker. Perfectly prepares a wide variety of surfaces for painting and helps block oil based stains to prevent discolouration of top coats.



Features and Benefits

- Low Odour
- Low VOC
- Excellent adhesion
- Stain blocking
- Excellent coverage
- Easy to use
- Suitable for multiple surfaces
- Multi-purpose, multi-surface
- Exterior and Interior use

Uses

For interior and exterior surfaces including paper-faced plasterboard, timber, MDF, brick, render, masonry, concrete, cement sheet, Zinalume, galvanised iron, PVC and previously painted surfaces.

✓ Interior ✓ Exterior

Precautions and Limitations

Temperature must be above 10°C and below 30°C during application and drying. Avoid exposure to steam and condensation for a minimum of 48 hours.

Typical Properties

Clean Up



Water

Clean Up Description

Clean brushes and equipment with water. Do not pour paint down the drain. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Please confirm local requirements. For more information on responsible disposal of paint and packaging visit paintback.com.au or painttakeback.co.nz.

Application Methods



Airless Spray



Brush



Roller

Application Guide

Surface Preparation

Previously painted surfaces: Remove loose or flaking paint. Fill cracks or holes with a filler and sand smooth. Lightly sand any satin or glossy surfaces to a flat/dull finish. Clean and dust down surface. Treat any existing mould by scrubbing with a scouring pad and bleach solution (1 part bleach to 3 parts water). Leave solution on the surface for 15 minutes then wash with clean water and allow to dry.

Timber: Fill nail holes with a flexible timber filler. Sand the surface as desired. Sand any raised wood fibres to a smooth finish. Brick, Masonry, Fibro & Fibre Cement Board: Leave masonry and cement based surfaces to cure for a minimum of 28 days before painting. Wash down with water using a stiff brush to remove all loose material. Fill holes with grouting cement. Use a 5% white vinegar solution to remove any white salts that have formed on the surface. Galvanised Iron & Zinalume® Clean with Selleys® Original Sugar Soap to remove grease and dust. Thoroughly wash off with water and allow to dry.

Application Procedure and Equipment

Application tools: Brush: High quality synthetic brush.
Roller: Medium pile (10-18mm) synthetic roller.
Spray: Up to 100mL per litre of water can be added to aid spraying.

Stir paint thoroughly. Surface must be clean, dry and free from dust, oils and grease. After following the preparation instructions, apply one coat of Prepare & Prime.

Clean brushes and equipment with water. Do not pour paint down the drain. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Please confirm local requirements. For more information on responsible disposal of paint and packaging visit paintback.com.au or painttakeback.co.nz

Recoat: Allow 2 hours to dry before applying topcoat. Allow longer under cooler or humid conditions.
Full paint hardness: 7 days, depending on conditions.

Health and Safety

SDS Number

SDS Link
[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.