

AUFW00031 Feast Watson Clear Varnish Matt

Introduction

Part A
870 94633

Description and Image

Feast Watson Clear Varnish is a clear, silky smooth, oil based polyurethane finish which provides excellent resistance to abrasion. The superior clarity of Clear Varnish highlights the beauty of natural timber. Feast Watson Proofint can be added to Clear Varnish to create a one step stain and varnish, or alternatively, the surface may be stained with Proofint prior to applying Clear Varnish. Clear Varnish is suitable for all interior woodwork including furniture, doors and windows, architraves, panelling and trim. Clear Varnish is not suitable for high traffic areas such as floors. For flooring use Feast Watson Floorclear.



Features and Benefits

- Polyurethane finish.
- Superior clarity.
- Excellent resistance to abrasion.
- Highlights the beauty of timber.

Uses

All interior woodwork including furniture, doors and windows, architraves, panelling and trim.

Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather
Interior only

Heat Resistance
Up to 100C

Water
Good

Typical Properties			
Gloss Level <10% at 60 degrees		Heat Thinner Mineral turpentine if spraying	
Colour Clear			
Components 1		Number of Coats 3	
Toxicity Lead free		V.O.C. Level < 575g/L	
Meets GBCA V.O.C. Requirements? No			
Touch Dry 6 hours			
Clean Up Description Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods  Brush  Roller  Spray			
Application Conditions		Solids by Volume	
		29	
		Min	Max
Recoat Time (min/hours)	8 hours		
Theoretical Spread Rate (m ² /L)	10	12	
Typical Property Notes Coverage 10 - 12m ² per litre. Drying Time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 6 hours Recoat: 8 hours			

Application Guide

Surface Preparation

New Timber

Sand to a smooth surface and remove all sanding dust before coating.

To achieve a super smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson Sanding Sealer and sand back as per the directions.

For naturally oily timbers, seal the timber with Feast Watson Proofseal as per the directions prior to application.

Previously Coated Timber

Previously varnished surfaces need to be sanded to a dull finish. Remove all sanding dust before coating.

Application Procedure and Equipment

Clear Varnish should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.

Apply Clear Varnish using a brush, roller or spray. If spraying Clear Varnish may be thinned by using 10% mineral turpentine. If applying by roller, use a short nap (5mm) mohair roller. Ensure edges and end grain are fully coated.

Allow 8 hours drying between coats. Sand lightly between coats with a fine sandpaper.

If applying over a previous varnish coating, two coats will be sufficient. For new timber, and if applying by spray, apply a minimum of three coats.

More coats may be applied for extra durability.

Staining

Apply Prooftint following label directions prior to the application of Clear Varnish.

Allow Prooftint to dry the recommended period before applying Clear Varnish.

Alternatively, add 10% Prooftint to the first coat of Clear Varnish, and allow 8 hours before applying the second coat.

If the desired colour is achieved in the first coat, apply subsequent coats without the Prooftint additive. To further develop colour intensity, Prooftint can be added to the subsequent coats.

Maintenance

Regularly monitor the surface for signs of colour loss or surface defects.

When required, lightly sand the surface and remove dust. Re-coat with additional coats of Clear Varnish as per application instructions.

Health and Safety

SDS Number

DLXGHSEN001013

SDS Link

[View SDS Link](#)

Using Safety Precautions

Flammable liquid and vapour. May be harmful if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness and dizziness.

Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs and oxidising agents. Keep cool. Do not empty into drains.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

87094633

Size:

250ml 500ml 1L

Weight:

0.30Kg 0.56Kg 1.05Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information[Product page](#)**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.