

AUCA00007 Cabot's Stain & Varnish Water Based Gloss

Introduction

Part A
538-line

Description and Image

Cabot's Stain & Varnish Water Based is a combined stain and clear varnish in one for all interior timber. It's easy to apply and is highly durable, resisting scuffing and scratching. As it's water based, it is fast drying so you can re-coat after only 2 hours and clean up is easy with water.



Features and Benefits

- Resists stains & scratches.
- Enhances timber grain.
- Fast recoat.
- Low odour.
- No topcoat required.
- Forms a durable protective finish which resists scuffing, scratching and household wear & tear.
- Enhances rather than hides the natural timber grain.
- Recoat after only 2 hours.
- Virtually no odour.
- Stain and durable clear finish all in one, meaning no top coat is required.

Uses

All bare interior timber.

Precautions and Limitations

Do not apply this product if the temperature is below 10°C or above 35°C.

Performance Guide

Weather
Interior use only.

Water
Good water resistance.

Abrasion
Resists scuffing, scratching and household wear & tear.

Typical Properties

Gloss Level

Gloss

Components

1

Number of Coats

3

V.O.C. Level

< 15g/L

Meets GBCA V.O.C. Requirements?

Yes

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tint required for non-factory packaged colours.

Touch Dry

30 Minutes

Clean Up



Water

Application Methods



Brush



Roller

Application Conditions

Solids by Volume

26

Min

Max

Recommended

Wet Film Per Coat (microns)

62

Dry Film Per Coat (microns)

16

Recoat Time (min/hours)

2 Hours

Theoretical Spread Rate (m²/L)

16

Typical Property Notes

Spreading rate

Up to 16 square metres per litre depending on the porosity and condition of the timber.

Drying and re-coat time

All timings quoted at 25C and 50% humidity. Cooler or humid conditions may require longer.

Application Guide

Surface Preparation

Note fill nail holes, cracks and other defects with Cabot's Wood Tone Putty after applying the first coat of this product for accurate colour matching. Remove stains, dirt, wax, grease and oil with mineral turpentine. Remove any polish with a suitable floor polish remover.

Bare timber

Sand the surface smooth using 180 - 240 grit sandpaper. Sand only in the direction of the grain. Remove all traces of sanding dust.

Previously coated timber

Completely remove the previous coating using a paint stripper or by sanding. Remove all traces of sanding dust.

Application Procedure and Equipment

Stir thoroughly with a broad flat paddle until pigment is mixed in and colour is uniform. Keep well stirred during use. If using more than one can, mix all cans together into a larger container to ensure colour uniformity. Apply with a good quality brush or roller. Apply three coats depending on the required depth of colour, allowing 2 hours between coats. For best results, sand between coats using 240 grit sandpaper.

Colour strength

If the desired colour is achieved after 1 or 2 coats of Cabot's Stain & Varnish Water Based, use Cabot's Cabothane Clear Water Based to complete the 3 coat system.

Maintenance

Regular inspection of all coated surfaces is recommended. Re-coating is recommended when the coating looks dull or tired. Clean with Cabot's Floor Clean following label instructions. Sand with 240 grit sandpaper then apply 1-2 coats.

Staining a floor

The natural colour of the timber will affect the finished colour of the stain. Always test the stain on an off cut or concealed part of the actual job before proceeding. Follow preparation steps above. Stain first with one coat of Cabot's Stain & Varnish Water Based using a 6 - 10mm nap roller. Additional coats can be applied if a deeper colour is required. Topcoat with Cabot's CFP Floor Water Based following label instructions.

Health and Safety

SDS Number
14282701

SDS Link
[View SDS Link](#)

Using Safety Precautions

Risk

Irritating to eyes and skin. Avoid contact with skin and eyes. Use only in well ventilated areas. If using indoors keep windows and doors open during use and while drying.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

538-line

Size:

Weight:

1L 500ml 250ml

1.2Kg 0.61Kg 0.33Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.