

## AUBG00015 Berger Gold Label Acrylic Matt

### Introduction

Part A  
**677-82357**

Approvals  
**APAS 0260/4**

### Description and Image

**Berger Gold Label® Acrylic Matt** is an interior washable acrylic paint with good opacity, adhesion and flexibility that provides a subdued low sheen finish.

### Features and Benefits

- Water based
- Very good opacity
- Low side sheen
- Same day recoat, easy clean up and low odour.
- Saves application time as two coat hiding allows rapid application.
- Hides substrate imperfections.

### Uses

Use Berger Gold Label Acrylic Matt as a subdued low sheen broad-wall and ceiling finish in lounges, bedrooms, etc.

✓ Interior ✓ Wall ✓ Ceiling






### Precautions and Limitations

**All preparation and painting must conform to AS2311: The Painting of Buildings.**

Do not apply at temperatures below 10C or when the temperature of surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Occasionally under steamy conditions an uneven appearance may develop early in the life of the coating. This is easily removed with a damp sponge and normally will not reappear. Seven days are required after application to develop maximum hardness and stain removal properties. Most stains and scuff marks can be removed by wiping or gentle rubbing with a sponge wet with detergent solution. Do not use abrasive cleaners. Tinter, if added, should be shaken and stirred in immediately and thoroughly.

### Performance Guide

Weather <b>Not recommended for exterior use.</b>	Salt <b>NA</b>
Heat Resistance <b>Resists up to 70C. May soften at higher temperatures.</b>	Water <b>Not recommended for high steam &amp; condensation areas.</b>
Solvent <b>Sensitive to aromatic hydrocarbons, alcohols, esters, ketones &amp; other strong solvents.</b>	Abrasion <b>Moderate abrasion resistance.</b>
Acid <b>NA</b>	Alkali <b>NA</b>

Typical Properties			
Gloss Level <b>2-5 at 60 degrees</b>		Thinner <b>Water</b>	
Colour <b>Can be tinted to a range of pastel colours using Dulux Professional Tinters up to 25ml per litre.</b>			
Components <b>1</b>			
Toxicity <b>Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.</b>		V.O.C. Level <b>&lt; 45g/L untinted</b>	
Touch Dry <b>20 Minutes</b>			
Clean Up  <b>Water</b>			
Clean Up Description Clean all equipment with clean water.			
Application Methods  <b>Air Spray</b>  <b>Airless Spray</b>  <b>Brush</b>  <b>Roller</b>			
Application Conditions		Solids by Volume	
		<b>37</b>	
	Min	Max	Recommended
Wet Film Per Coat (microns)	<b>73</b>	<b>73</b>	<b>73</b>
Dry Film Per Coat (microns)	<b>27</b>	<b>27</b>	<b>27</b>
Recoat Time (min/hours)	<b>2 Hours</b>	<b>Indefinite</b>	
Theoretical Spread Rate (m <sup>2</sup> /L)	<b>13.7</b>	<b>13.7</b>	<b>13.7</b>

## Application Guide

### Surface Preparation

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thorough sanding and wipe clean with a damp cloth, then apply sealer or undercoat as required.

### Application Procedure and Equipment

#### Brush, roller, conventional or airless spray

Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action.

#### Brush/Roller

Apply two full even coats direct from the container. Under hot conditions or on very absorbent surfaces, up to 100ml of clean water may be added per litre to assist application. Use a short nap roller (eg rolana or orlon). Avoid excessive brushing or rolling back into paint which has been drying some minutes.

#### Airless/Conventional Spray

Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre water to aid atomisation.

## Health and Safety

SDS Number

**36504, 0**

SDS Link

[View SDS Link](#)

**Please refer to SDS Link. In case of emergency, please call 1800 220 770.**

## Transport and Storage

Pack A

**677-82357**

Size:

Weight:

**4 Litre 10 Litre 15 Litre**

**6.1 Kg 15.1 Kg 21.2 Kg**

Flash Point

**NA**

UN Number

**NA**

Dangerous Goods Class

**NA**

Package Group

**NA**

## Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.