

AUBG00015 Berger Gold Label Acrylic Matt

Introduction

Part A
677-82357

Approvals
APAS 0260/4

Description and Image

Berger Gold Label® Acrylic Matt is an interior washable acrylic paint with good opacity, adhesion and flexibility that provides a subdued low sheen finish.

Features and Benefits

- Water based
- Very good opacity
- Low side sheen
- Same day recoat, easy clean up and low odour.
- Saves application time as two coat hiding allows rapid application.
- Hides substrate imperfections.

Uses

Use Berger Gold Label Acrylic Matt as a subdued low sheen broad-wall and ceiling finish in lounges, bedrooms, etc.

✓ Interior ✓ Wall ✓ Ceiling

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not apply at temperatures below 10C or when the temperature of surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Occasionally under steamy conditions an uneven appearance may develop early in the life of the coating. This is easily removed with a damp sponge and normally will not reappear. Seven days are required after application to develop maximum hardness and stain removal properties. Most stains and scuff marks can be removed by wiping or gentle rubbing with a sponge wet with detergent solution. Do not use abrasive cleaners. Tinter, if added, should be shaken and stirred in immediately and thoroughly.

Performance Guide

Weather Not recommended for exterior use.	Salt NA
Heat Resistance Resists up to 70C. May soften at higher temperatures.	Water Not recommended for high steam & condensation areas.
Solvent Sensitive to aromatic hydrocarbons, alcohols, esters, ketones & other strong solvents.	Abrasion Moderate abrasion resistance.
Acid NA	Alkali NA

Typical Properties			
Gloss Level 2-5 at 60 degrees		Thinner Water	
Colour Can be tinted to a range of pastel colours using Dulux Professional Tinters up to 25ml per litre.			
Components 1			
Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.		V.O.C. Level < 45g/L untinted	
Touch Dry 20 Minutes			
Clean Up Water			
Clean Up Description Clean all equipment with clean water.			
Application Methods Air Spray Airless Spray Brush Roller			
Application Conditions	Solids by Volume		
	<input type="text" value="37"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="73"/>	<input type="text" value="73"/>	<input type="text" value="73"/>
Dry Film Per Coat (microns)	<input type="text" value="27"/>	<input type="text" value="27"/>	<input type="text" value="27"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="13.7"/>	<input type="text" value="13.7"/>	<input type="text" value="13.7"/>

Application Guide

Surface Preparation

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thorough sanding and wipe clean with a damp cloth, then apply sealer or undercoat as required.

Application Procedure and Equipment

Brush, roller, conventional or airless spray

Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action.

Brush/Roller

Apply two full even coats direct from the container. Under hot conditions or on very absorbent surfaces, up to 100ml of clean water may be added per litre to assist application. Use a short nap roller (eg rolana or orlon). Avoid excessive brushing or rolling back into paint which has been drying some minutes.

Airless/Conventional Spray

Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre water to aid atomisation.

Health and Safety

SDS Number

36504, 0

SDS Link

[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

677-82357

Size:

Weight:

4 Litre 10 Litre 15 Litre

6.1 Kg 15.1 Kg 21.2 Kg

Flash Point

NA

UN Number

NA

Dangerous Goods Class

NA

Package Group

NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.