

## AUPP00008 Porter's Paints Eggshell Acrylic

### Introduction

Part A  
**PB1-LINE**

### Description and Image

Porter's Eggshell Finish is a superior quality acrylic paint that gives walls and other surfaces a low reflective finish with an elegant, matt sheen level that maximises depth of colour. This chic finish is fully washable for interiors and highly durable for exteriors. Fast drying with low odour.



### Features and Benefits

- Fully washable
- Low Odour
- Low Volatile Organic Content (VOC)
- Meets the assessment criteria set by Ecospecifier™ and is therefore eligible for Green Star credits.
- Water wash up.

### Standards And Certifications



Global Green Tag  
Certified: GreenRate  
Level A

#### Standards and Certifications

For details on these standards and certifications please reference the 'Approvals' section at the beginning of this document. Please contact your DuluxGroup representative for specific information on ESD credits / points.

**Uses**

Interior and exterior walls, trim, doors and accessories. Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

✓ Interior ✓ Exterior ✓ Wall

**Precautions and Limitations**

Do not apply in high humidity, below 10°C or above 30°C. Check colour before use.

**Typical Properties**

Thinner  
**Water**

Colour  
Available in a wide range of colors tinted from Standard, Bright White, Mid, Deep, Clear, Red, Magenta and Black bases or ask our colourist for your own custom colour.

Acrylic Range Base:

Ultra Flat:	Eggshell: Standard Mid Deep Clear Black Red Magenta	Low Sheen:	Aqua Satin Enamel:
-------------	--	------------	--------------------

Aqua Gloss Enamel:	Stone Paint Fine:	Stone Paint Coarse:	
--------------------	-------------------	---------------------	--

Components <b>1</b>	Number of Coats <b>2</b>
------------------------	-----------------------------

V.O.C. Level  
**<5g/L VOC's (untinted), Except Red base <14 g/L (untinted)**

Touch Dry  
**1 hour ( at 25 Deg C and 50% relative Humidity)**

Clean Up  
 **Water**

Clean Up Description  
Clean brushes and equipment with water. Do not pour paint down the drain. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Please confirm local requirements. For more information on responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au) or [painttakeback.co.nz](http://painttakeback.co.nz).

Application Methods  
 **Airless Spray** **Brush** **Roller**

Application Conditions	Solids by Volume
	<input type="text" value="38"/>
	Min <span style="margin-left: 150px;">Max</span> <span style="margin-left: 150px;">Recommended</span>

Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<b>80</b>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<b>30</b>
Recoat Time (min/hours)	<b>2 hrs</b>	<b>indefinite</b>	<b>2 hours</b>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text"/>	<input type="text"/>	<b>13</b>

**Application Guide**

Surface Preparation

**New/unpainted substrates**

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted timber, sand smooth and dust down, and apply 1 or 2 coats Porter's Prepare & Prime. Allow 2 hours dry time before overcoating.

On new unpainted plasterboard sheeting spot prime all joints then apply by brush, roller or spray 1 or 2 coats Porter's Prepare & Prime. Allow 2 hours dry time before overcoating.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Prepare & Prime. Allow 2 hours dry time before recoating or overcoating with top coat.

On bare masonry surfaces such as, render or brick, spot prime all repaired areas with Porter's Limeproof Undercoat Sealer, then apply 1 coat of same to entire area by brush, medium nap roller or spray. Touch dry in 1 hour. Allow 6 hours dry time before recoating or over-coating.

On bare metal surfaces use Porter's Universal Primer. Suitable for use as a metal primer, including galvanized iron, wrought iron, steel, aluminium, stainless steel, copper and brass. Universal Primer contains anti-corrosive pigments to inhibit rust and corrosion and a resin that delivers the extra adhesion required for metallic substrates. Please read the Universal Primer specification prior to use. Apply 1 or 2 coats. Touch dry in 20 minutes. Allow minimum 2 hours dry time between coats and 24 hours dry time before overcoating

**Previously painted substrates**

Provided the surface is clean and sound, Porter's Eggshell Finish is self-priming and can be applied directly over previously painted surfaces. (Except oil-based paints or polyurethanes). All varnishes, polyurethanes or surfaces previously painted with oil-based enamel paint should be thoroughly sanded to remove gloss and to create a "keyed" surface. Loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Prepare & Prime, then apply one coat of same to entire area. Allow 2 hours dry time before recoating or overcoating with top coat.

Application Procedure and Equipment




**APPLICATION:**

Stir thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point. Do not apply if the surface temperature is greater than 30°C or below 10°C, or likely to fall below 10°C during the application or drying period. Stir thoroughly prior to use. Apply two coats by brush, spray or medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

Health and Safety	
SDS Number <b>DLXGHSEN001630</b>	SDS Link <a href="#">View SDS Link</a>
Using Safety Precautions Keep out of reach of children. Use only in well ventilated areas. Wash hands after use.	
<b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b>	

Transport and Storage	
Pack A <b>PB1-LINE</b>	
Size: <b>500ml, 1 litre, 2 litre, 4 litre, 10 litre</b>	Weight: <b>0.80kg, 1.55kg, 3.04kg, 5.98kg, 14.5</b>
Flash Point <b>NA</b>	UN Number <b>NA</b>
Dangerous Goods Class <b>Not classified as Dangerous Goods for transport by Road &amp; Rail and Marine. Not classified as Dangerous Goods for transport by Air.</b>	Package Group <b>NA</b>

Images		
		
Walls: Porter's Eggshell Finish in Chintz Grey	Walls: Porter's Eggshell Finish in Hailstorm. Trim: Porter's Aquasatin Enamel in Popcorn	Walls: Porter's Eggshell Finish in Gunmetal Grey. Trim: Porter's Aquasatin Enamel in Popcorn

#### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.