

## AUPR00030 Dulux Professional Acrylic Primer

### Introduction

Part A  
**664-84187**

Approvals  
**APAS 0183**

### Description and Image

**Dulux Professional Acrylic Primer** is a high quality 100% acrylic water based primer designed for use on interior and exterior substrates, particularly suited to timber, brick and masonry.



### Features and Benefits

- Easy sanding
- Excellent adhesion
- Off-white colour
- Tannin stain blocking
- Produces a smooth surface of even porosity ready for topcoating
- Sticks well to porous substrates to increase life of paint systems
- Improves the opacity of light coloured topcoats
- Reduces the likelihood of tannin staining through topcoats

### Uses

Use Dulux Professional Acrylic Primer to produce a smooth even surface on porous substrates such as timber, brick and masonry. Will help reduce likelihood of tannin bleed on new timber. Can be topcoated with any water based or oil based product.






### Precautions and Limitations

**All preparation and painting must conform to AS2311: The Painting of Buildings.**

Do not overspread or exceed 14 square metres per litre per coat. In hot weather, rinse brush every half hour or use two and keep one standing in water.

Do not apply if temperature is under 10C, or when temperature of surface may fall below 10C during the drying period, otherwise film formation will not be complete and poor properties will result.

Performance Guide	
Weather <b>Excellent when used as part of approved system.</b>	
Heat Resistance <b>Up to 70C.</b>	Water <b>Resists rain and condensation when used as part of approved system.</b>
Solvent <b>Sensitive to aromatic hydrocarbons, alcohols and ketones.</b>	Abrasion <b>Good when topcoated.</b>

Typical Properties	
Gloss Level <b>Low Sheen</b>	Thinner <b>Water</b>
Colour <b>Off-white</b>	
Components <b>1</b>	
Toxicity <b>Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.</b>	V.O.C. Level <b>&lt;45 g/L</b>
Meets GBCA V.O.C. Requirements? <b>Yes</b> Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.	
Touch Dry <b>30 Minutes</b>	
Clean Up  <b>Water</b>	
Clean Up Description Clean all equipment with water.	
Application Methods  <b>Air Spray</b>  <b>Airless Spray</b>  <b>Brush</b>  <b>Roller</b>	
Application Conditions	Solids by Volume <input type="text" value="36.4"/>
	Min Max Recommended
Wet Film Per Coat (microns)	<input type="text" value="71"/> <input type="text" value="71"/> <input type="text" value="71"/>
Dry Film Per Coat (microns)	<input type="text" value="26"/> <input type="text" value="26"/> <input type="text" value="26"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/> <input type="text" value="Indefinite"/> <input type="text"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="14"/> <input type="text" value="14"/> <input type="text" value="14"/>

**Application Guide**

Surface Preparation

- Do not apply paint if the temperature is below 10°C or likely to fall below 10°C during the drying period.

All surfaces must be thoroughly clean and free of all loose dirt, surface chalk, grease, mould, mildew and wax, loose or flaking paint and efflorescence. New timber surfaces should be sanded smooth and dusted down prior to priming. Fill nail holes, imperfections and cracks with a suitable filler, sand and dust off.

Application Procedure and Equipment

**Brush, roller, conventional or airless spray.**  
**Note:** Spray application is not recommended for priming timber substrates as penetration into surface is not as good.

Stir contents thoroughly before and during use. Apply direct from the can. May be applied to dampened surfaces. If applied over dry, porous surfaces, dampen surface before applying.

**Brush**  
 Wet brushes with water prior to use to avoid clogging. Apply a full even coat direct from the container. Under hot conditions it may be necessary to thin with up to 100ml per litre of clean water.

**Roller**  
 Using a medium nap roller apply a full even coat direct from the container and finish by light parallel strokes with a dry roller.

**Airless/Conventional Spray**  
 Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.

**Health and Safety**

SDS Number <b>DLXGHCEN001258</b>	SDS Link <a href="#">View SDS Link</a>
<b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b>	

**Transport and Storage**

Pack A <b>664-84187</b>	
Size: <input type="text" value="10L only"/>	Weight: <input type="text" value="13.5 Kg"/>
Flash Point <b>NA</b>	UN Number <b>NA</b>
Dangerous Goods Class <b>NA</b>	Package Group <b>NA</b>

#### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.