AUFW00023 Feast Watson Mastertouch Polish

Introduction

Part A
917 94669

Description and Image

Feast Watson MASTERTOUCH POLISH is unique combination of refined oils to restore and enhance the natural beauty of timber. MASTERTOUCH POLISH
will rejuvenate coatings and help to diminish fine scratches. MASTERTOUCH POLISH is silicone free to help protect the timber coating.

Features and Benefits

- Use on all timber surfaces
- Silicon free
- Can be used as a floor polish
- Easily re-coated

Uses

Use FEAST WATSON Mastertouch Polish to restore the natural beauty of timber finishes back to a bright lustre. Mastertouch removes all fine scratches that develop on floors and furniture from general wear and tear.

Precautions and Limitations

Not suitable for uncoated timber.
Floors will be slippery whilst wet.
Soak application cloths in water before disposal.

Performance Guide

Weather **For interior use only**	Heat Resistance **Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat.**
Water **Good water resistance.**	Abrasion **Moderate resistance to abrasion.**

Typical Properties

Colour
Clear

Components	Number of Coats
1	**1**

Toxicity	V.O.C. Level
Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.	**< 130g/L**

Touch Dry
2 hours

Clean Up

Water

Clean Up Description
Warm soapy water

Application Methods

Pad

Mop or cloth

Application Guide

Surface Preparation

Bare Timber
Not suitable for uncoated timber.

Coated Timber
Surfaces must be clean & dry.

Application Procedure and Equipment

Floors
Pour MASTERTOUCH Polish directly onto a water dampened applicator or mop.
Wipe sparingly over the floor. Polish off using a soft dry cloth.
Warning: Floors will be slippery whilst wet.

Furniture
Pour MASTERTOUCH Polish directly onto a soft, damp cloth.
Wipe sparingly over the timber furniture. Polish off using a soft dry cloth.

Health and Safety

SDS Number	SDS Link
4160	

Using Safety Precautions
Avoid contact with skin and eyes. Provide adequate ventilation. Wash hands after use.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

917-94669

Size:	Weight:
375ml 250ml	400g 300g

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.