# AUFW00108 Feast Watson Hard Wax

## Introduction

Part A
**91A-line**

## Description and Image

**Feast Watson Hard Wax** rejuvenates and protects coated interior timber furniture. Can be used to fill small scratches apply with a soft cloth. Allow 5-15 minutes to dry then buff with a clean cloth or steel wool (000 or 0000) to achieve the desired lustre. Use Hard Wax black on dark timbers and finishes to enrich the colour, or on light finishes for an antique look.




## Features and Benefits

- Premium carnauba wax
- Rejuvenates and protects

## Uses

Interior timber furniture

## Performance Guide

Weather
**Interior use only**

## Typical Properties

Colour
**Available in Natural, Brown and Black**

Number of Coats
**1 minimum**

V.O.C. Level
**<645g/L**

Meets GBCA V.O.C. Requirements?
**No**

Clean Up Description
Mineral turpentine

Application Methods

Soft cloth

## Application Guide

Surface Preparation

Ensure surface is clean and dry.

Application Procedure and Equipment

Apply a thin even coat using a soft cloth.
Rub briskly in a circular motion to create friction to soften the wax.
Leave for 5-15 minutes, then buff with a clean cloth or steel wool (000 or 0000) to achieve the desired lustre.
Finish by rubbing in the direction of the grain.

Use Hard Wax Natural on light timbers and finishes;
Use Hard Wax Brown on darker timbers and finishes;
Use Hard Wax Black on dark timbers and finishes to enrich the colour or on light finishes for an antique look.

## Health and Safety

| SDS Number | SDS Link |
|---|---|
| **DLXGHSEN003408** | **View SDS Link** |

Using Safety Precautions
Causes skin irritation. May cause an allergic skin reaction.
Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray.. Wash hands, face and all exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing, gloves, eye/face protection and suitable respirator.

**Please refer to SDS Link. In case of emergency, please call 1800 220 770.**

## Transport and Storage

Pack A

**91A-line**

| Size: | Weight: |
| --- | --- |
| 125g | 0.15Kg |

**Please refer to the Safety Data Sheet for full safety, health and transportation information.**

## Further Information

**Product page**

### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.