

AUPC00005 Dulux Protective Coatings LUXAFLOOR CP Low Sheen

Introduction

Part A
760-H0200

Description and Image

LUXAFLOOR® CP is a clear, colourless, moisture curing, aliphatic (non-yellowing), clear urethane coating for brush, or roller application. A high performance clear finish coat for natural wooden floors and ground concrete.
When applied to diamond ground concrete, LUXAFLOOR® CP enhances the aggregate particles in the floor, imparting a contemporary "polished concrete" look that also protects against staining from spills.
When LUXAFLOOR® CP Low Sheen is applied as the final coat over LUXAFLOOR® CP Gloss, it imparts an elegant low sheen finish to the floor.

Features and Benefits

- Single Pack
- Medium build, non-yellowing moisture curing polyurethane
- UV resistant – contains protective UV absorbers
- Fast curing over a wide temperature range
- Suitable for interior and exterior use
- Non yellowing
- Suitable for both industrial and commercial flooring
- Easy to apply

Uses

A single pack polyurethane for Industrial and commercial floor coating that enhances and protects the natural concrete look, giving a "polished concrete" appearance..

Performance Guide

Weather Very good	Heat Resistance Up to 120°C dry heat
Water Very good resistance to fresh and salt water but not suitable for immersion	Abrasion Good when fully cured

Typical Properties

Components

1

Shelf Life

1 year

Mixing Ratio

Not applicable

Pot Life

Not applicable

Clean Up

Dulux® Urethane Thinner (965-63023)

Clean Up Description

Dulux® Urethane Thinner (965-63023)

Application Methods



Brush



Roller

Typical Property Notes

10.8 square metres per litre equals 40 µm dry film thickness

NOTE: Practical spreading rates will vary depending on such factors as application method, ambient conditions, surface porosity and roughness.

Application Guide

Surface Preparation

Concrete: Concrete should be at least 28 days old before coating. Remove all laitance, curing compounds, oil, grease and other surface contaminants. Diamond grind, track or light shot-blast concrete floors to remove laitance and provide a suitable profile. Remove all dust by vacuum cleaning. Fill any large cracks or voids using Luxepoxy® Filler.

Application Procedure and Equipment

Shake can before use. Decant sufficient for immediate use into a roller tray or working pot. Seal original container to prevent moisture exposure. Decant only that sufficient for 30 minutes use and do not return unused product to original container.

Apply by floor brush or mohair roller. Sand lightly between coats to remove defects. Thinning not normally recommended. When brushing and rolling additional coats may be required to attain the specified thickness.

Transport and Storage

Size:

10 litre can

Weight:

1.01 kg/litre

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.