

AUCA00022 Cabot's Interior Stain Water Based

Introduction

Part A
527-line

Description and Image

Cabot's Interior Stain Water Based is an easy to use, deep rich stain that transforms the colour of interior timber doors, windows, trim and furniture. It must be over coated with Cabot's Cabothane Clear Water Based to give the protection and durability required on interior timber.



Features and Benefits

- Enhances timber grain.
- Easy to apply.
- Fast recoat.
- Low odour.
- Clear top coat required.
- Enhances rather than hides the natural timber grain.
- Simply brush on and wipe off.
- Recoat after only 2 hours.
- Virtually no odour.
- Top coat with Cabot's Cabothane Clear Water Based to ensure adequate durability and protection.

Uses




Bare timber doors, windows, trim and furniture.

Precautions and Limitations

Do not apply this product if the temperature is below 10°C or above 35°C.

Performance Guide

Weather
Interior use only.

Typical Properties			
Gloss Level Matt			
Components 1	Number of Coats 1		
V.O.C. Level < 15g/L			
Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry 30 minutes			
Clean Up  Water			
Application Methods  Brush  Roller Rag			
Application Conditions	Solids by Volume <input type="text" value="10"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="80"/>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="8"/>
Recoat Time (min/hours)	<input type="text" value="2 hours"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="12"/>
Typical Property Notes Spreading rate Up to 12 square metres per litre depending on the porosity and condition of the timber. Drying and re-coat time All timings quoted at 25C and 50% humidity. Cooler or humid conditions may require longer.			

Application Guide

Surface Preparation

Note fill nail holes, cracks and other defects with Cabot's Wood Tone Putty after applying the first coat of this product for accurate colour matching. Remove stains, dirt, wax, grease and oil with mineral turpentine. Remove any polish with a suitable floor polish remover.

Bare timber

Sand the surface smooth using 180 - 240 grit sandpaper. Sand only in the direction of the grain. Remove all traces of sanding dust.

Previously coated timber

Completely remove the previous coating using a paint stripper or by sanding. Remove all traces of sanding dust.

Important

The natural colour of the timber will affect the finished colour of the stain. The clear coating used to seal the stain may also have some affect on the final colour. Always test the stain on an off cut or concealed part of the actual job before proceeding.

Staining a floor

For the best method of staining a floor, please refer to the Cabot's Stain & Varnish range.

Application Procedure and Equipment

Roller, Brush, Rag

Stir thoroughly with a broad flat paddle until pigment is mixed in and colour is uniform. Keep well stirred during use. If using more than one can, mix all cans together into a larger container to ensure colour uniformity. Apply with a good quality brush, roller or lint free rag and work the stain evenly into the grain. Allow to set for 1 - 5 minutes then rub with a clean soft cloth using a circular motion to remove any excess stain and produce an even coloured surface. The intensity of the colour will depend on porosity of timber and the length of time before the stain is wiped off. Allow 2 hours drying time. Apply Cabot's Cabothane Clear Water Based as a top coat following label instructions.

Maintenance

Regular inspection of all coated surfaces is recommended.

Health and Safety

SDS Number
22571

SDS Link
[View SDS Link](#)

Using Safety Precautions

Provide adequate ventiation. If using indoors keep windows and doors open during use and while drying.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
527-line

Size:

Weight:

1L 500ml 250ml

1.2Kg 0.62Kg 0.33Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.