

## AUIN00495 Intergrain UltraClear Interior Satin

### Introduction

Line Shade  
**521-94803**

Variant

### Description and Image

Intergrain UltraClear Interior is a tough, clear, water-based finish for use on interior timber. Incorporating UV absorbers, UltraClear Interior provides greater protection against the colour change of timbers by shielding against UV rays. UltraClear Interior is resistant to mild/non abrasive household chemicals, water splash, is lower odour than solvent based coatings, and will not yellow. Easy to apply and fast drying, UltraClear Interior allows several coats to be applied in one day. Use on interior timber, including doors, windows, furniture, and joinery. UltraClear Interior is ideal for maintaining the timber's natural colour, especially with pale timbers such as Pine, Victorian Ash, and Cedar.

Note: UltraClear Interior is not suitable for coating areas subject to foot traffic.

### Features and Benefits

- UV protection for interior timber
- Highly durable
- Lower odour than solvent based products
- Fast drying

### Uses

- Interior timber
- Ceilings
- Hand railings
- Vertical surfaces
- Doors
- Windows
- Furniture
- Joinery

### Precautions and Limitations

This product has been developed for application to internal timber components and is not suitable for walk on surfaces.

Wherever possible, protect the timber from the elements during installation, avoiding exposure and pooling water where applicable.

Pooling water must be appropriately squeegeed away from the surface as soon as practical.

\*Subject to specific preparation requirement





### Performance Guide

Weather

**Interior use only, suitable for internal areas exposed behind glazing systems**

Water  
**Good**

Abrasion  
**Good**

Typical Properties			
Gloss Level <b>Satin</b>			
Colour <b>Clear</b>			
Components <b>1</b>		Number of Coats <b>2-3</b>	
V.O.C. Level <b>&lt;15 g/L</b>			
Meets GBCA V.O.C. Requirements? <b>Yes</b> Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry <b>1 hour</b>			
Clean Up  <b>Water</b>			
Clean Up Description Clean brushes and equipment with water			
Application Methods  <b>Brush</b>  <b>Roller</b>  <b>Spray</b>			
Application Conditions	Solids by Volume <input type="text" value="31.79"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="65"/>	<input type="text"/>	<input type="text"/>
Dry Film Per Coat (microns)	<input type="text" value="20.93"/>	<input type="text"/>	<input type="text"/>
Recoat Time (min/hours)	<input type="text" value="2"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="15.19"/>	<input type="text"/>	<input type="text"/>
Typical Property Notes This product is supplied ready for use. Stir well before use			

Application Guide
Surface Preparation <ul style="list-style-type: none"> <li>Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point. Do not apply if the surface temperature is greater than 40°C or below 10°C, or likely to fall below 10°C during the application or drying period.</li> </ul>

Health and Safety	
SDS Number <b>DLXGHSEN004915</b>	SDS Link
<p>Using Safety Precautions SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.</p> <p>Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.</p>	
<p><b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b></p>	

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.