AUCA00347 Cabot's Exterior Cleaner

Introduction

Part A
57CW0555

Description and Image

Cabot's Exterior Cleaner is your go-to solution for cleaning timber and surrounding outdoor surfaces. Specifically designed to be used on your coated timber, in-between protective oil, stain or varnish applications, it is also suitable for all exterior surfaces.

Ideal for decks, outdoor furniture, pergolas, and fences, it effectively removes dirt, grease and grime without harming your timber coatings. Its versatility extends beyond wood, making it suitable for use on concrete, bricks, paving, and tiles – perfect for keeping your entire outdoor living area spotless. Available in 1L, 4L sizes and a convenient 500ml spray option.

*When used diluted and in accordance with instructions.



Features and Benefits

- Everyday cleaner designed for use on all exterior timber
- Safe for plants* and does not contain bleach or chlorine
- Removes dirt and grime without damaging existing coatings
- Fast and easy to use
- Also safe for use on concrete, bricks, paving and tiles
- Water clean up and 10 minute rinse off
- Contains a pleasant blue gum extract scent

Uses

For use on all exterior timber, while also safe for use on concrete, bricks, paving and tiles.

Precautions and Limitations

Not suitable for bare or greyed timber. Do not use this product within 2 weeks of coating any exterior timber.

Performance Guide

Weather **Not applicable**	Heat Resistance **Not applicable**
Water **Not applicable**	Abrasion **Not applicable**

Typical Properties

Colour
Pale yellow

Components
1 pack

Mixing Ratio
1:10

Clean Up

Water

Application Methods

Brush

Cabot's Deck Prep Brush

Application Conditions

	Min	Max	Recommended
Theoretical Spread Rate (m²/L)			40

Typical Property Notes
Diluted Cabot's Exterior Cleaner will cover up to 40 m²/L.

Application Guide

Surface Preparation

1. Sweep away leaves, dirt and debris.
2. Hose down exterior surface, ensuring surface is damp prior to application.

Application Procedure and Equipment

1. Shake contents before use.
2. Mix 1 part Cabot's Exterior Cleaner with 10 parts water. Covers 40m²/L when diluted.
3. Apply generously to the timber with Cabot's Deck Prep brush. Scrub vigorously.
4. Leave the solution on the timber for 5-10 minutes. Do not allow to dry on surface, keep damp with the cleaning solution as required.
5. Lightly scrub the surface before rinsing, then rinse off with water using a high pressure or garden hose. Heavily soiled or very dirty surfaces may require repeat application. If using a high pressure hose or power washer, use the lowest setting to avoid damaging the surface.

Health and Safety	
SDS Number **DLXGHSEN004818**	SDS Link **View SDS Link**

Using Safety Precautions
Risks: Undiluted form may cause an allergic skin reaction and serious eye damage.

Keep out of reach of children. Read carefully and follow all instructions.
Wear protective gloves/protective clothing including eye/face protection.
If medical advice is needed, have product container or label at hand.

IF ON SKIN: Wash with plenty of water and soap.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
57CW0555

Size:	Weight:
500ML, 1L, 4L	**590G, 1.092Kg, 4.198Kg**

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.