

**AUIN00040 Intergrain UltraPrep Timber Cleaner****Introduction**

Part A  
**552-W0537**

**Description and Image**

**Intergrain UltraPrep™ Timber Cleaner** is a high strength timber treatment that prepares timber prior to coating. This high performance, bio-degradable formula is specially designed to be garden safe<sup>^</sup>, and will not damage surrounding surfaces such as exterior paint, metal or plastic<sup>^</sup>. Use Intergrain UltraPrep Timber Cleaner to remove surface contaminants prior to coating. The cleaner will help to restore and prepare weathered, grey, rust or tannin stained, mould or mildew affected timber to a clean appearance ready for coating. <sup>^</sup>When diluted and applied as instructed and provided rinsed off immediately after contact. Rinse residue will not harm surrounding plants and grass.

**Features and Benefits**

- High strength concentrate
- Contains natural bio-degradable acids

**Uses**

Prior to coating all exterior timber including decking, outdoor furniture, cladding, screening and fences.  
Not suitable for interior applications.

**Precautions and Limitations**

Exterior use only. Not suitable for interior use.  
Wear waterproof gloves and safety glasses.  
Avoid contact with painted, glass, concrete or metal surfaces and vegetation. Protect areas not to be cleaned.  
May be corrosive to metals. Rinse off thoroughly if contact occurs.

**Typical Properties**

V.O.C. Level  
**<10g/L**

Meets GBCA V.O.C. Requirements?

**Yes**

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.

Clean Up



**Water**

Application Methods

Stiff bristle brush.

Application Conditions

Min

Max

Recommended

Theoretical Spread Rate (m<sup>2</sup>/L)

**10**

Typical Property Notes

MIX RATIO

1 part UltraPrep Timber Cleaner to 4 parts water

COVERAGE

Up to 10m<sup>2</sup>/L of concentrate.

### Application Guide

#### Surface Preparation

Remove surface dirt by sweeping or washing down with water.

#### Application Procedure and Equipment

Shake Intergrain UltraPrep Timber Cleaner thoroughly.

Mix one part Intergrain UltraPrep Timber Cleaner to four parts water in a plastic container. For severely stained surfaces a stronger solution or repeat applications may be necessary. Tannin rich timbers may also require repeat applications; wash until the water used to rinse off is clear.

Wet the timber surfaces to be cleaned with water.

Apply Intergrain UltraPrep Timber Cleaner mixture generously to the timber with a stiff bristle brush. Scrub the timber vigorously. Spot cleaning should be avoided to prevent patchy results.

Leave mixture on the timber for 10-15 minutes. If necessary, apply more mixture to keep timber damp throughout this period, do not allow mixture to dry.

Rinse off surface thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner (recommended for large areas or badly discoloured timber). Failure to thoroughly rinse off the mixture may result in timber discolouration under clear finishes.

**Note:** After cleaning, some timber species will appear lighter due to loss of water soluble extractives. Richer colour is generally restored on application of the finish.

#### Help & advice

Australia – 1800 630 285

[www.intergrain.com.au](http://www.intergrain.com.au)

NZ – 0800 222 687

[www.intergrain.co.nz](http://www.intergrain.co.nz)

For detailed project specifications or a Safety Data Sheet, contact Intergrain Help & Advice or visit our website.

### Health and Safety

SDS Number

**DLXGHSEN003477**

SDS Link

[View SDS Link](#)

#### Using Safety Precautions

Harmful if swallowed and in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

Keep out of reach of children. Read the label before opening or using.

Slippery when spilt. Avoid breathing mist, vapours or spray. Wear protective clothing, gloves and eye/face protection and suitable respiratory as required. Contaminated work clothing should not be allowed out of the workplace. Wash hands, face and all exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Store in a closed container. Store away from oxidising agents and foodstuffs. Avoid release to the environment.

**Please refer to SDS Link. In case of emergency, please call 1800 220 770.**

### Transport and Storage

Pack A

**55294814**

Size:

Weight:

**1L 4L 10L**

**1.15Kg 4.28Kg 10.83Kg**

**Please refer to the Safety Data Sheet for full safety, health and transportation information.**

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

**WHERE LEAD MAY BE PRESENT:** The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.