AUCA00348 Cabot's Cabot's Wood Floor Polish

Introduction

Part A
57MW0556

Description and Image

Cabot's Wood Floor Polish is specially formulated to bring dull timber floors back to life. Just apply our simple mop-on solution to refresh and maintain wooden floorboards. Safe for coated wood surfaces — including hardwood timber, hybrid, engineered, and parquetry floors — this polish revives their natural beauty, reduces the appearance of scratches, and helps prolong the life of coated surfaces.

Whether your floors are looking a little tired or you simply want to maintain their brilliance between protective recoats, Cabot's Wood Floor Polish is the ideal solution. Fast and easy to apply with a mop, it delivers visible results keeping your timber floors looking their best every day.

Features and Benefits

- Fast and easy to use
- Restores shine
- Reduces the appearance of scratches and marks
- Prolongs the life of coated surfaces
- Does not damage existing coatings
- Safe for wood floors

Uses

For use on all sealed wood floors, including hardwood, softwood, hybrid, engineered and parquetry floors.

Precautions and Limitations

Ensure the surface is clean and dry, and avoid use on unsealed or non-recommended flooring types
Do not apply product if temperature is below 10 degrees or above 30 degrees or is likely to reach these temperatures during the drying period. Equally, relative humidity should not exceed 85%.

Performance Guide

Weather **Not applicable**	Heat Resistance **Not applicable**
Water **Not applicable**	Abrasion **Not applicable**

Typical Properties

Gloss Level **Not applicable**	Heat Thinner **Not applicable**
Colour **Milky white in appearance and dries clear**	
Components **1 pack**	Number of Coats **1**
Toxicity **Not applicable**	V.O.C. Level **0.933 g/L**

Meets GBCA V.O.C. Requirements?
Yes

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.

Touch Dry
1 hour

Clean Up

Water

Application Methods

Pad

Mop sponge

Application Conditions

	Min	Max	Recommended
Recoat Time (min/hours)			1 hour
Theoretical Spread Rate (m²/L)			60

Application Guide

Surface Preparation

Cabot's Wood Floor Polish should only be applied to a dry and well cured surface (a new coating should be at least 4 weeks old). Ensure the surface is thoroughly cleaned with Cabot's Wood Floor Cleaner prior to using Cabot's Wood Floor Polish.

Application Procedure and Equipment

IMPORTANT: Do not shake before use
1. Apply Cabot's Wood Floor Polish undiluted with a sponge mop or Cabot's Lambswool applicator. Avoid introducing bubbles when applying and do not allow pools of liquid to form.
2. Allow the surface to dry for 1 hour.
3. Repeat application if a higher gloss level is desired.

Health and Safety

SDS Number	SDS Link
DLXGHSEN004814	**View SDS Link**

Using Safety Precautions
Risk: Harmful in contact with skin and if swallowed. Irritating to eyes.
Keep out of reach of children.
Read carefully and follow all instructions.
Wash hands, face and all exposed skin thoroughly after handling. Wear protective gloves/protective clothing including eye/face protection.
If medical advice is needed, have product container or label at hand.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
57MW0556

Size:	Weight:
1L	**1.140 Kg**

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.