

AUCA00344 Cabot's Wood Floor Cleaner

Introduction

Part A
57CW0552

Description and Image

Cabot's Wood Floor Cleaner is purpose-made for wood, combining effective cleaning with the care your wooden floors need. Formulated for use with the Cabot's Wood Floor Signature Spray Mop, it's ready to use straight from the bottle – no mixing or dilution required.

Its fast-drying formula not only makes cleaning quicker but also ensures a streak-free* finish. With the natural freshness of Lemon Myrtle extract, your home feels clean and inviting after every use. Most importantly, it provides antibacterial protection, killing 99.9% of germs[^] to keep your living spaces hygienic. Available in 1L, 4L sizes and a convenient 500ml spray for spot cleaning, Cabot's Wood Floor Cleaner makes it easy to clean your floors every day.

*When used with Cabot's Wood Floor Signature Spray Mop in accordance with instructions.

[^]When left on the surface for 5 minutes.



Features and Benefits

- Safe for all sealed wood floors
- Fast drying*
- Antibacterial and kills 99.9% of germs[^]
- Streak free finish*
- Does not damage existing coatings
- Ready to use, no mixing or dilution required

Uses

For use on all sealed wood floors including hardwood, softwood, hybrid, engineered wood and parquetry floors.

Precautions and Limitations

Store product in a cool, dry place away from direct sunlight. Keep out of reach of children and pets.

Not suitable for bare timber. Do not use on freshly coated timber within 2 weeks of application.

Performance Guide

| | |
|----------------------------------|--|
| Weather Not Applicable | Heat Resistance Not Applicable |
| Water Not Applicable | Abrasion Not Applicable |

Typical Properties

Colour

Pale yellow

Components

1 Pack

Clean Up

**Water****Application Methods**

Cabot's Wood Floor Signature Spray Mop and Trigger spray for the 500mL.

Application Guide**Surface Preparation**

Vacuum or sweep the floor before you begin to mop.

Application Procedure and Equipment

1. Fill the Cabot's Wood Floor Signature Spray Mop bottle with Cabot's Wood Floor Cleaner. Do not fill above indicated maximum fill line. Replace cap on bottle securely to prevent any leaks, and attach onto Cabot's Wood Floor Signature Spray Mop.
2. For best results, dampen the pad with water prior to cleaning. Wring out excess water so the pad feels damp but does not drip.
3. Pull the Cabot's Wood Floor Signature Spray Mop trigger to spray a light mist across the floor. You may need to squeeze the trigger a few times initially to begin the flow of cleaner.
4. Mop back and forth using approximately one spray per square metre.
5. For best results, work in small sections to ensure the cleaner dries quickly and evenly.

Health and Safety

SDS Number

DLXGHSEN004813

SDS Link

[View SDS Link](#)**Using Safety Precautions**

Risks: May cause an allergic skin reaction and eye irritation.

Keep out of reach of children. Read carefully and follow all instructions. Avoid breathing mist, or spray.

Wash hands, face and all exposed skin thoroughly after handling.

If medical advice is needed, have product container or label at hand.

IF ON SKIN: Wash with plenty of water and soap.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs and eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

57CW0552

Size:

500mL, 1L, 4L

Weight:

587G, 1.14Kg, 4.104Kg**Please refer to the Safety Data Sheet for full safety, health and transportation information.****Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.