

AUFW00019 Feast Watson Feast Watson Floor Polish Gloss

Introduction

Part A
872 94655

Description and Image

Feast Watson Floor Polish is a water based floor polish designed to impart added shine and protection to the floor.

Features and Benefits

- Water based
- Quick drying
- Good wet-out
- Easy clean-up. Low odour.
- Walk on in 1 hour.
- Will stick to most surfaces

Uses

Use Feast Watson Floor polish over all sealed non porous surfaces.

Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather Interior only	Heat Resistance Up to 700C
Water Good splash resistance	Abrasion Good

Typical Properties			
Gloss Level Gloss			
Colour Clear			
Components 1		Number of Coats 1 or 2	
Toxicity Lead free.		V.O.C. Level < 70g/L	
Clean Up  Water			
Application Methods  Pad			
Application Conditions			
	Min	Max	Recommended
Recoat Time (min/hours)	1 hour		
Typical Property Notes			
Coverage Approximately 60 square metres per litre.			
Drying Time Drying times are given at 25°C and 50% relative humidity. Lower temperatures, higher humidity or heavy coats can lead to extended drying times.			

Application Guide

Surface Preparation

Ensure the surface is thoroughly clean and free from dust. Floor Polish should be applied only to a dry and well cured surface (approx. 3-4 weeks old). Do not shake prior to use.

Application Procedure and Equipment

Apply Floor Polish with a clean sponge mop or lambs wool applicator. The surface should be just dampened with Floor Polish and spread evenly, do not allow pools of liquid to form. Allow the surface to dry and repeat application until desired gloss level is achieved.

Maintenance

Wash surface at regular intervals using Feast Watson Floorclean. When surface begins to look worn, re-coat with Floor Polish.

Removing Feast Watson Floor Polish

If required, old layers of the polish may be stripped off using Cloudy Ammonia; this should be available in hardware stores and supermarkets.

- Apply undiluted Cloudy Ammonia to the floor.
- Leave for 5 minutes.
- Do not allow the Cloudy Ammonia solution to dry out.
- Do not flood the floor with the solution.
- Mop up solution and then thoroughly clean surface with a clean mop and fresh water.
- Repeat if necessary.
- Allow surface to dry.

Once the old polish has been removed, a new coat of Feast Watson Floor Polish can be applied, following the label instructions.

Health and Safety

SDS Number
3792

SDS Link
[View SDS Link](#)

Using Safety Precautions

Avoid eye and repeated or prolonged skin contact. Provide adequate ventilation. Keep windows and doors open during use and while product drying. Do not pour leftover polish down drain. Keep unwanted polish in a sealed container for disposal via chemical waste collection. Store in a cool place and out of direct sunlight. Keep container closed when not in use.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
872-94655

Size:

Weight:

1 Litre 4 Litre

1.2 Kg 4.6 Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.