

AUAV00011 Dulux Avista Internal Flooring Decorative Flakes

Introduction

Line Shade
FD400 Line

Product Overview and Image

Avista Internal Flooring Decorative Flake is a pigmented polymer flake individually coloured of irregular shape and sizes. Available in a selection of colours.



Features and Benefits

- Use with Avista Epoxy Flooring products for a decorative flake floor
- For commercial and domestic flooring applications

Uses

The Avista decorative flake flooring system can be used for garages, kitchens, laundries and rumpus rooms. It can also be used for commercial applications such as shops, foyers, offices and schools.

Typical Properties

Application Methods

Hand

Application Guide

Surface Preparation

Apply Avista Internal Flooring Epoxy products as per data sheet application instructions

Application Procedure and Equipment

Remove flake from box and place in a suitable clean, dry bucket.

Immediately after applying Avista coating and while it is still tacky, walk out on the job wearing spiked shoes and evenly sprinkle the dry flake over the surface.

Allow Avista Epoxy to cure (approximately

hours depending on conditions prevailing). Once completely dry, scrape any excess flake from the surface or sand any high points. This ensures no loose or sharp protruding flake is left on the surface. Broom and discard excess flake.

Vacuum thoroughly.

Apply top coat sealer as per relevant data sheet instructions.

| Health and Safety | |
|--|---|
| SDS Number PAR000558 | SDS Link View SDS Link |
| Please refer to SDS Link. In case of emergency, please call 1800 220 770. | |

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.